



FEATURES:

- Wide 4:1 Input Voltage Range
- High efficiency up to 88%
- Remote On/Off
- Standard 1"x1" Package
- 1500 VDC Isolation
- Operating Temperature -40°C to +85°C
- Over Voltage, Over load protection
- Output Short Circuit Protection



Models
Single output

Model	Input Voltage (V)	Output Voltage (V)	Output Current max (mA)	Max Capacitive Load(uF)	Efficiency (%)
AM10CW-2403S-FZ	9-36	3.3	2200	3300	82
AM10CW-2405S-FZ	9-36	5	2000	2200	85
AM10CW-2412S-FZ	9-36	12	830	680	88
AM10CW-2415S-FZ	9-36	15	660	330	88
AM10CW-2424S-FZ	9-36	24	410	100	87
AM10CW-4803S-FZ	18-75	3.3	2200	3300	80
AM10CW-4805S-FZ	18-75	5	2000	2200	84
AM10CW-4812S-FZ	18-75	12	830	680	87
AM10CW-4815S-FZ	18-75	15	660	330	87
AM10CW-4824S-FZ	18-75	24	410	100	87

Models
Dual output

Model	Input Voltage (V)	Output Voltage (V)	Output Current max (mA)	Max Capacitive Load(uF)	Efficiency (%)
AM10CW-2405D-FZ	9-36	±5	±1000	±1000	85
AM10CW-2412D-FZ	9-36	±12	±410	±470	88
AM10CW-2415D-FZ	9-36	±15	±330	±220	87
AM10CW-4805D-FZ	18-75	±5	±1000	±1000	84
AM10CW-4812D-FZ	18-75	±12	±410	±470	87
AM10CW-4815D-FZ	18-75	±15	±330	±220	87

NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified.

Input Specifications

Parameters	Nominal	Typical	Maximum	Units
Voltage range	24	9-36		VDC
	48	18-75		
Filter	Pi			
Start up time	77			ms
Absolute Maximum Rating	24	50		VDC
	48	100		
Peak Input Voltage time	100			ms
On/Off control	ON –Open or 3.5 to 12V/<0.2mA			
	OFF –Short to pin 2 (-Vin) or 0 to 0.7V			
Idle Input Current	At OFF state		12	mA
Input reflected current	62			mA p-p
Transient response settling time	50% load step change		550	µs
Transient response deviation	di/dt=0.8A/µs		≤5	%
	3.3Vou		≤6	

Isolation Specifications

Parameters	Conditions	Typical	Maximum	Units
Tested I/O voltage		1500		VDC
Resistance	500VDC		>1000	MOhm
Capacitance		1100		pF

Output Specifications

Parameters	Conditions	Typical	Maximum	Units
Voltage accuracy		±1		%
Over voltage protection	3.3 Vout	3.9		V
	5 Vout	6.2		
	12 Vout	15		
	15 Vout	18		
	24 Vout	27		
Short Circuit protection		Continuous		
Short circuit restart		Auto-Recovery		
Line voltage regulation	LL to HL at full load	±1		% of Vin
Load voltage regulation (Single)	0% to Full load	±1		%
Load voltage regulation (Dual)	Balanced Load	±0.5		%
	Unbalanced load 25 to 100% load	±5		
Temperature coefficient			±0.02	%/°C
Ripple & Noise	20MHz Bandwidth	80		mV p-p


General Specifications

Parameters	Conditions	Typical	Maximum	Units
Switching frequency	100% load	330kHz		KHz
Operating temperature	With derating above 60°C	-40 to +85		°C
Storage temperature		-55 to +125		°C
Maximum case temperature			105	°C
Cooling		Natural convection		
Humidity			95	% RH
Case material		Nickel-coated copper		
Weight		17.4		g
Dimensions (L x W x H)		1 x 1 x 0.4 inches	25.4 x 25.4 x 10.2 mm	
MTBF		>1,580,000 hrs (MIL-HDBK -217F, Ground Benign, t=+25°C)		

Pin Out Specifications

Pin	Single	Dual
1	+V input	+V input
2	-V Input	-V Input
3	On/Off Control	On/Off Control
4	+V Output	+V Output
5	No Pin	Common
6	-V output	-V output


Dimensions



Notes:

- All dimensions are typical in millimeters (inches).
- Pin Pitch Tolerance ±0.35 (±0.014)
- Case Tolerance ±0.50 (±0.02)

Derating



NOTE: 1. Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to www.aimtec.com for the most current product specifications. 2. Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. 3. Mechanical drawings and specifications are for reference only. 4. All specifications are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. 5. Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. 6. This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet. 7. Warranty is in accordance with Aimtec's standard Terms of Sale available at www.aimtec.com.