

CSD23285F5 -12V P 沟道 FemtoFET™ MOSFET

1 特性

- 低导通电阻
- 低 Q_g 和 Q_{gd}
- 超小尺寸
 - 1.53mm x 0.77mm
 - 0.50mm 焊盘间距
- 薄型封装
 - 厚度为 0.36mm
- 集成型 ESD 保护二极管
 - 额定值 > 4kV 人体放电模式 (HBM)
 - 额定值 > 2kV 组件充电模式 (CDM)
- 无铅且无卤素
- 符合 RoHS

2 应用

- 针对工业负载开关应用进行了优化
- 针对通用开关应用进行了优化

3 说明

该 29mΩ、-12V N 沟道 FemtoFET™ MOSFET 技术经过设计和优化，能够最大限度地减小在许多手持式和移动应用中占用的空间。这项技术能够在替代标准小信号 MOSFET 的同时大幅减小封装尺寸。




图 3-1. 典型器件尺寸

产品概要

| $T_A = 25^\circ\text{C}$ | | 典型值 | 单位 |
|--------------------------|----------------|-------------------------|----|
| V_{DS} | 漏源电压 | - 12 | V |
| Q_g | 栅极电荷总量 (-4.5V) | 3.2 | nC |
| Q_{gd} | 栅极电荷 (栅极到漏极) | 0.48 | nC |
| $R_{DS(on)}$ | 漏源导通电阻 | $V_{GS} = -1.5\text{V}$ | 64 |
| | | $V_{GS} = -1.8\text{V}$ | 49 |
| | | $V_{GS} = -2.5\text{V}$ | 38 |
| | | $V_{GS} = -4.5\text{V}$ | 29 |
| $V_{GS(th)}$ | 阈值电压 | - 0.65 | V |

器件信息(1)

| 器件 | 数量 | 介质 | 封装 | 配送 |
|-------------|------|--------|----------------------------|-----|
| CSD23285F5 | 3000 | 7 英寸卷带 | Femto | 卷带式 |
| CSD23285F5T | 250 | | 1.53mm x 0.77mm 无引线 SMD | |

(1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。

绝对最大额定值

| $T_A = 25^\circ\text{C}$ | | 值 | 单位 |
|--------------------------|---------------|---------------|------------------|
| V_{DS} | 漏源电压 | - 12 | V |
| V_{GS} | 栅源电压 | - 6 | V |
| I_D | 持续漏极电流(1) | - 3.3 | A |
| | 持续漏极电流(2) | - 5.4 | |
| I_{DM} | 脉冲漏极电流(1) (3) | - 31 | A |
| P_D | 功率耗散(1) | 0.5 | W |
| | 功率耗散(2) | 1.4 | |
| $V_{(ESD)}$ | 人体放电模型 (HBM) | 4000 | V |
| | 充电器件模型 (CDM) | 2000 | |
| T_J 、 T_{stg} | 工作结温、 贮存温度 | - 55 至 150 | $^\circ\text{C}$ |

- (1) $R_{\theta JA} = 245^\circ\text{C}/\text{W}$ (覆铜面积最小时的典型值)。
 (2) $R_{\theta JA} = 90^\circ\text{C}/\text{W}$ (覆铜面积最大时的典型值)。
 (3) 脉冲持续时间 $\leq 100 \mu\text{s}$ ，占空比 $\leq 1\%$ 。




图 3-2. 顶视图



Table of Contents

| | | | |
|---|----------|--|----------|
| 1 特性 | 1 | 6 Device and Documentation Support | 7 |
| 2 应用 | 1 | 6.1 Receiving Notification of Documentation Updates..... | 7 |
| 3 说明 | 1 | 6.2 Trademarks..... | 7 |
| 4 Revision History | 2 | 7 Mechanical, Packaging, and Orderable Information | 8 |
| 5 Specifications | 3 | 7.1 Mechanical Dimensions..... | 8 |
| 5.1 Electrical Characteristics..... | 3 | 7.2 Recommended Minimum PCB Layout..... | 9 |
| 5.2 Thermal Information..... | 3 | 7.3 Recommended Stencil Pattern..... | 9 |
| 5.3 Typical MOSFET Characteristics..... | 3 | | |

4 Revision History

Changes from Revision A (July 2017) to Revision B (February 2022) Page

| | |
|---|---|
| • 将超薄型封装要点中的厚度从 0.35mm 更改为 0.36mm..... | 1 |
| • 将超薄型封装图片中的厚度从 0.35mm 更新为 0.36mm..... | 1 |
| • Changed ultra-low profile image height from 0.35 mm to 0.36 mm..... | 8 |
| • Added FemtoFET Surface Mount Guide note..... | 9 |

Changes from Revision * (August 2016) to Revision A (July 2017) Page

| | |
|---|---|
| • Added 表 7-1 to the 节 7.1 section..... | 8 |
|---|---|

5 Specifications

5.1 Electrical Characteristics

$T_A = 25^\circ\text{C}$ (unless otherwise stated)

| PARAMETER | | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------------|----------------------------------|--|-------|-------|-------|------------|
| STATIC CHARACTERISTICS | | | | | | |
| BV_{DSS} | Drain-to-source voltage | $V_{GS} = 0\text{ V}, I_{DS} = -250\ \mu\text{A}$ | -12 | | | V |
| I_{DSS} | Drain-to-source leakage current | $V_{GS} = 0\text{ V}, V_{DS} = -9.6\text{ V}$ | | | -100 | nA |
| I_{GSS} | Gate-to-source leakage current | $V_{DS} = 0\text{ V}, V_{GS} = -5\text{ V}$ | | | -25 | nA |
| $V_{GS(th)}$ | Gate-to-source threshold voltage | $V_{DS} = V_{GS}, I_{DS} = -250\ \mu\text{A}$ | -0.40 | -0.65 | -0.95 | V |
| $R_{DS(on)}$ | Drain-to-source on-resistance | $V_{GS} = -1.5\text{ V}, I_{DS} = -1\text{ A}$ | | 64 | 130 | m Ω |
| | | $V_{GS} = -1.8\text{ V}, I_{DS} = -1\text{ A}$ | | 49 | 80 | |
| | | $V_{GS} = -2.5\text{ V}, I_{DS} = -1\text{ A}$ | | 38 | 47 | |
| | | $V_{GS} = -4.5\text{ V}, I_{DS} = -1\text{ A}$ | | 29 | 35 | |
| g_{fs} | Transconductance | $V_{DS} = -1.2\text{ V}, I_{DS} = -1\text{ A}$ | | 8.9 | | S |
| DYNAMIC CHARACTERISTICS | | | | | | |
| C_{iss} | Input capacitance | $V_{GS} = 0\text{ V}, V_{DS} = -6\text{ V},$ $f = 1\text{ MHz}$ | | 483 | 628 | pF |
| C_{oss} | Output capacitance | | | 305 | 397 | pF |
| C_{rss} | Reverse transfer capacitance | | | 37 | 48 | pF |
| R_G | Series gate resistance | | | 17 | | Ω |
| Q_g | Gate charge total (-4.5 V) | $V_{DS} = -6\text{ V}, I_{DS} = -1\text{ A}$ | | 3.2 | 4.2 | nC |
| Q_{gd} | Gate charge gate-to-drain | | | 0.48 | | nC |
| Q_{gs} | Gate charge gate-to-source | | | 0.66 | | nC |
| $Q_{g(th)}$ | Gate charge at V_{th} | | | 0.40 | | nC |
| Q_{oss} | Output charge | $V_{DS} = -6\text{ V}, V_{GS} = 0\text{ V}$ | | 4.8 | | nC |
| $t_{d(on)}$ | Turnon delay time | $V_{DS} = -6\text{ V}, V_{GS} = -4.5\text{ V},$ $I_{DS} = -1\text{ A}, R_G = 2\ \Omega$ | | 15 | | ns |
| t_r | Rise time | | | 5 | | ns |
| $t_{d(off)}$ | Turnoff delay time | | | 30 | | ns |
| t_f | Fall time | | | 13 | | ns |
| DIODE CHARACTERISTICS | | | | | | |
| V_{SD} | Diode forward voltage | $I_{SD} = -1\text{ A}, V_{GS} = 0\text{ V}$ | | -0.73 | -1 | V |

5.2 Thermal Information

$T_A = 25^\circ\text{C}$ (unless otherwise stated)

| THERMAL METRIC | | MIN | TYP | MAX | UNIT |
|-----------------|---|-----|-----|-----|--------------------|
| $R_{\theta JA}$ | Junction-to-ambient thermal resistance ⁽¹⁾ | | 90 | | $^\circ\text{C/W}$ |
| | Junction-to-ambient thermal resistance ⁽²⁾ | | 245 | | |

- (1) Device mounted on FR4 material with 1-in² (6.45-cm²), 2-oz (0.071-mm) thick Cu.
(2) Device mounted on FR4 material with minimum Cu mounting area.

5.3 Typical MOSFET Characteristics

$T_A = 25^\circ\text{C}$ (unless otherwise stated)




图 5-1. Saturation Characteristics




图 5-2. Transfer Characteristics




图 5-3. Transient Thermal Impedance




图 5-4. Gate Charge





图 5-6. Threshold Voltage vs Temperature






图 5-8. Normalized On-State Resistance vs Temperature






图 5-10. Maximum Safe Operating Area (SOA)




图 5-11. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.


6.2 Trademarks

FemtoFET™ is a trademark of Texas Instruments.
所有商标均为其各自所有者的财产。

7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 Mechanical Dimensions




4222132/A 06/2015

- A. All linear dimensions are in millimeters (dimensions and tolerancing per AME T14.5M-1994).
- B. This drawing is subject to change without notice.
- C. This package is a PB-free solder land design.

表 7-1. Pin Configuration


| POSITION | DESIGNATION |
|----------|-------------|
| Pin 1 | Gate |
| Pin 2 | Source |
| Pin 3 | Drain |

7.2 Recommended Minimum PCB Layout



- A. All dimensions are in millimeters.
- A. For more information, see [FemtoFET Surface Mount Guide \(SLRA003D\)](#).

7.3 Recommended Stencil Pattern



- A. All dimensions are in millimeters.

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead finish/ Ball material (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|-----------------|------|-------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| CSD23285F5 | ACTIVE | PICOSTAR | YJK | 3 | 3000 | RoHS & Green | NIAU | Level-1-260C-UNLIM | -55 to 150 | 4S | Samples |
| CSD23285F5T | ACTIVE | PICOSTAR | YJK | 3 | 250 | RoHS & Green | NIAU | Level-1-260C-UNLIM | -55 to 150 | 4S | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CSD23285F5 | PICOST AR | YJK | 3 | 3000 | 178.0 | 8.4 | 0.92 | 1.68 | 0.42 | 4.0 | 8.0 | Q1 |
| CSD23285F5 | PICOST AR | YJK | 3 | 3000 | 180.0 | 8.4 | 0.92 | 1.68 | 0.42 | 4.0 | 8.0 | Q1 |
| CSD23285F5T | PICOST AR | YJK | 3 | 250 | 178.0 | 8.4 | 0.92 | 1.68 | 0.42 | 4.0 | 8.0 | Q1 |
| CSD23285F5T | PICOST AR | YJK | 3 | 250 | 180.0 | 8.4 | 0.92 | 1.68 | 0.42 | 4.0 | 8.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CSD23285F5 | PICOSTAR | YJK | 3 | 3000 | 220.0 | 220.0 | 35.0 |
| CSD23285F5 | PICOSTAR | YJK | 3 | 3000 | 182.0 | 182.0 | 20.0 |
| CSD23285F5T | PICOSTAR | YJK | 3 | 250 | 220.0 | 220.0 | 35.0 |
| CSD23285F5T | PICOSTAR | YJK | 3 | 250 | 182.0 | 182.0 | 20.0 |

重要声明和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 [TI 的销售条款](#) 或 [ti.com](#) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265

Copyright © 2022，德州仪器 (TI) 公司