FIBOX
Enclosing innovations

MNX PC 300/150 ZG

Sample photo

Order symbol:	PC 300/150 ZG	**EAN**:	6418074061515
Product nbr:	6017338	**El. number**:	
Description:	Enclosure, PC	Finland:	3435614
Remarks:	Grey cover	Electric No. Denmark:	8212027983
		Electric No. Sweden:	6017338

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	**Length**	**Width**	**Height**
mm:	360	255	152
inch:	14.2	10.0	6.0

Materials:	
Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover screws material:	Polyamide
Cover colour:	RAL 7035 -light grey
Cover screws colour:	Grey
Gasket material:	Polyurethane

Temperatures:	
Temperature °C (short term):	-40 … 120 °C
Temperature °C (continuous):	-40 … 80 °C
Temperature °F (short term):	-40 … 250 °F
Temperature °F (continuous):	-40 … 175 °F

Accessories:	
MIV 300	Mounting plate (Galvanized steel)

Accessories:	
MIV 200	Mounting plate (Galvanized steel)
MIV 150	Mounting plate (Galvanized steel)
MIN 20	DIN-15 Mounting rail
MIN 15	DIN-15 Mounting rail
MIV 30	DIN-35 Mounting rail
MIV 20	DIN-35 Mounting rail
MIV 15	DIN-35 Mounting rail
FP 10674	

Rating:

Ingress Protection (EN 60529): IP66/IP67
Impact Resistance (EN 62262): IK08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): 1
UV resistance: UL 508
Flammability Rating: UL 746C 5"
Glow Wire Test (IEC 695-2-1) °C: 960
NEMA Class: NEMA 1, 4, 4X and 6



© Fibox Oy, Data subject to change without notice (printed: 4.11.2019)