

guided drive DFM-40-100-P-A-KF

Part number: 170942

★ Core product range

With integrated guide.

The proximity switch, type SMTSO-8E, can be used with this product with stroke lengths equal to or greater than 50 mm. The corresponding mounting kit, type SMB-8E, is mounted inwardly or outwardly.

FESTO



Data sheet

| Feature | Value |
|---|---|
| Centre of gravity distance from working load to yoke plate | 50 mm |
| Stroke | 100 mm |
| Piston diameter | 40 mm |
| Operating mode of drive unit | Yoke |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Guide | Recirculating ball bearing guide |
| Design structure | Guide |
| Position detection | For proximity sensor |
| Operating pressure | 1.5 ... 10 bar |
| Max. speed | 0.8 m/s |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 0 - No corrosion stress |
| Ambient temperature | -5 ... 60 °C |
| Impact energy in end positions | 0.7 Nm |
| Max. force F _y | 1,130 N |
| Max. force F _y static | 1,260 N |
| Max. force F _z | 1,130 N |
| Max. force F _z static | 1,260 N |
| Max. torque M _x | 49.74 Nm |
| Max. torque M _x static | 55.44 Nm |
| Max. torque M _y | 28.83 Nm |
| Max. torque M _y static | 32.13 Nm |
| Max. torque M _z | 28.83 Nm |
| Max. torque M _z static | 32.13 Nm |
| Max. permissible torque load M _x as a function of the stroke | 7.74 Nm |
| Max. useful load as a function of the stroke at defined distance x _s | 138 N |
| Theoretical force at 6 bar, return stroke | 686 N |
| Theoretical force at 6 bar, advance stroke | 754 N |
| Moving mass | 1,433 g |
| Product weight | 3,265 g |
| Centre of gravity of the moving mass as a function of the stroke | 62.1 mm |
| alternative connections | See product drawing |
| Pneumatic connection | G1/8 |
| Materials note | Free of copper and PTFE Conforms to RoHS |
| Material cover | Wrought Aluminium alloy |
| Material seals | NBR |
| Material housing | Wrought Aluminium alloy |
| Material piston rod | High alloy steel, non-corrosive |