

MLF1608C330KTD00


Applications Commercial Grade Feature Multilayer Multilayer

> Shield Magnetic Shield

> > Ferrite Core

Ferrite Core Series MLF Series / MLF1608 Type

Status Production











Size	
Length(L)	1.60mm +/-0.15mm
Width(W)	0.80mm +/-0.15mm
Thickness(T)	0.80mm +/-0.15mm
Recommended Land Pattern (A)	0.60mm Nom.
Recommended Land Pattern (B)	0.80mm Nom.
Recommended Land Pattern (C)	0.80mm Nom.

Electrical Characteristics	
Inductance	33uH +/-10% at 1MHz
Rated Current	2mA
Self-Resonant Frequency [Min.]	10MHz
Self-Resonant Frequency [Typ.]	30MHz
Q [Min.]	20 at 1MHz
Q [Typ.]	40 at 1MHz
DC Resistance [Nom.]	1.4Ω
DC Resistance [Max.]	2.2Ω

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 85degC
Soldering Method	Reflow, Iron Soldering
AEC Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	4000Pcs Min.
Weight	0.004g


[•]This PDF document was created based on the data listed on the TDK Corporation website.


[•]All specifications are subject to change without notice.



MLF1608C330KTD00


Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)






MLF1608C330KTD00







MLF1608C330KTD00

MLF1608C330KTD00

[•]This PDF document was created based on the data listed on the TDK Corporation website.

[•]All specifications are subject to change without notice.



MLF1608C330KTD00

Characteristic Graphs (This is reference data, and does not guarantee the product's characteristics.)

DC Bias Characteristic	Temperature Characteristic
no data available	no data available

Temperature Rise by DC

no data available

[•]This PDF document was created based on the data listed on the TDK Corporation website.

[•]All specifications are subject to change without notice.