





# MLZ2012M4R7WT000

Applications		Commercial Grade
Feature		Multilayer
		Magnetic Shield
		Ferrite Core
Series	MLZ Series / MLZ2012 Type	
Status	Production	



Size	
Length(L)	2.00mm +/-0.20mm
Width(W)	1.25mm +/-0.20mm
Thickness(T)	0.85mm +/-0.20mm
Recommended Land Pattern (A)	0.80mm Nom.
Recommended Land Pattern (B)	1.00mm Nom.
Recommended Land Pattern (C)	1.20mm Nom.


Electrical Characteristics	
Inductance	4.7uH +/-20% at 2MHz
Rated Current (L Change) [Max.]	180mA (50% Down)
Rated Current (Temperature Rise) [Typ.]	500mA (20degC Rise)
Self-Resonant Frequency [Min.]	
DC Resistance [Nom.]	300mΩ
DC Resistance [Max.]	390mΩ

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-55 to 125degC
Soldering Method	Flow, Reflow, Iron Soldering
AEC Q200	No
Packing	Punched (Paper)Taping [180mm Reel]
Package Quantity	4000Pcs Min.
Weight	0.01g


•This PDF document was created based on the data listed on the TDK Corporation website.  
 •All specifications are subject to change without notice.

# MLZ2012M4R7WT000


**Characteristic Graphs** (This is reference data, and does not guarantee the product's characteristics.)




**MLZ2012M4R7WT000**



**MLZ2012M4R7WT000**



**MLZ2012M4R7WT000**




**MLZ2012M4R7WT000**

•This PDF document was created based on the data listed on the TDK Corporation website.  
 •All specifications are subject to change without notice.

# MLZ2012M4R7WT000

**Characteristic Graphs** (This is reference data, and does not guarantee the product's characteristics.)



•This PDF document was created based on the data listed on the TDK Corporation website.  
•All specifications are subject to change without notice.