Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15WF104J03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104J03RC

NCP15WF104J03RC

In Production   Recommended   RoHS   REACH

Appearance & Shape

Electrode
(Ag System + Ni Plating + Sn Plating)   (in mm)

Applications

Limited Usage	Consumer Grade
Other Usage	1. Temperature compensation for transistor, IC and crystal oscillator in mobile communications 2. Temperature sensor for rechargeable batteries 3. Temperature compensation of LCD 4. Temperature compensation in general use of electric circuits

Packaging Information

Packaging	Specifications	Standard Packing Quantity
RC	180mm Paper Tape	10000

Features

1. Excellent solderability and high stability in environment
2. Excellent long time aging stability
3. High accuracy in resistance and B-Constant
4. Reflow soldering possible
5. Same B-constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)
   Easy to use smaller size in the circuits
6. Lead is not contained in the product.
7. NCP series are recognized by UL/cUL (UL1434, File No.E137188).

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata
INNOVATOR IN ELECTRONICS

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15WF104J03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104J03RC

NCP15WF104J03RC

Specifications

|	
Resistance (25℃)	100kΩ
Resistance Value Tolerance (at 25℃)	±5%
B-Constant (25/50℃)	4250K
B-Constant (25/50℃) Tolerance	±1%
B-Constant(25/80℃) (Reference Value)	4303K
B-Constant(25/85℃) (Reference Value)	4311K
B-Constant(25/100℃) (Reference Value)	4334K
Max. Voltage	5V
Maximum Operating Current (25℃)	0.032mA
Typical Dissipation Constant (25℃)	1mW/℃
Operating Temperature Range	-40℃ to 125℃
Size Code (in mm)	1.0x0.5mm
Size Code (in inch)	0.4x0.2inch
Shape	SMD
Mass	0.0012g

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

muRata
INNOVATOR IN ELECTRONICS

URL : https://www.murata.com/

Last updated02/16/2021

Product Search Data Sheet

INNOVATOR IN ELECTRONICS

Note: This datasheet may be out of date.

Please download the latest datasheet of NCP15WF104J03RC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCP15WF104J03RC

NCP15WF104J03RC

Product Data

Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

URL : https://www.murata.com/

Last updated02/16/2021