

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCU18XH103F60RB

## NCU18XH103F60RB












## Appearance & Shape







### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

Easy to use smaller size in the circuits

- 6. Lead is not contained in the product.
- 7. UL/cULcertified product.(UL1434, File No. E137188)



## **Applications**

Limited Usage Consumer Grade



# Packaging Information

Packaging	Specifications	Standard Packing Quantity
RB	180mm Paper Tape	4000

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

#### Note: This datasheet may be out of date. Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCU18XH103F60RB

# NCU18XH103F60RB



# **Specifications**

Resistance (25°C)	10kΩ	
, ,	10/22	
Resistance Value Tolerance	±1%	
(at 25°C)		
B-Constant (25/50°C)	3380K	
B-Constant (25/50°C)	±1%	
Tolerance		
B-Constant(25/80°C)	3428K	
(Reference Value)		
B-Constant(25/85°C)	3434K	
(Reference Value)		
B-Constant(25/100°C)	3455K	
(Reference Value)	0.00.1	
Max. Voltage	5V	
Maximum Operating Current	0.1mA	
(25°C)	O. IIIIA	
Typical Dissipation Constant	1mW/°C	
(25°C)		
Operating Temperature	-40°C to 125°C	
Range	70 C 10 120 C	
Size Code (in mm)	1.6x0.8mm	
Size Code (in inch)	0.6x0.3inch	
Shape	SMD	
Mass	0.0047g	
MSL	1	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Product Search Data Sheet


Note: This datasheet may be out of date. Please download the latest datasheet of NCU18XH103F60RB from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=NCU18XH103F60RB

# NCU18XH103F60RB



## **Product Data**





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

