Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18XH103J60RB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCU18XH103J60RB

# NCU18XH103J60RB












### Appearance & Shape







### **Applications**

Limited Usage	Consumer Grade
	Temperature compensation for transistor, IC and crystal oscillator in
	mobile communications 2. Temperature
Other Usage	sensor for rechargeable batteries 3.
	Temperature compensation of LCD 4.
	Temperature compensation in general
	use of electric circuits



### Packaging Information

Packaging	Specifications	Minimum Order Quantity
RB	180mm Paper Tape	4000



#### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18XH103J60RB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCU18XH103J60RB

# NCU18XH103J60RB



# **Specifications**

Resistance (25°C)	10kΩ	
Resistance Value Tolerance	±5%	
(at 25°C)		
B-Constant (25/50°C)	3380K	
B-Constant (25/50°C)		
Tolerance	±1%	
B-Constant(25/80°C)	0.40017	
(Reference Value)	3428K	
B-Constant(25/85°C)	3434K	
(Reference Value)		
B-Constant(25/100°C)	3455K	
(Reference Value)	34331	
Max. Voltage	5V	
Maximum Operating Current	0.4. A	
(25°C)	0.1mA	
Typical Dissipation Constant	4 18/96	
(25°C)	1mW/°C	
Operating Temperature	-40°C to 125°C	
Range		
Size Code (in mm)	1.6x0.8mm	
Size Code (in inch)	0.6x0.3inch	
Shape	SMD	
Mass	0.0047g	

2 of 3

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of NCU18XH103J60RB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NCU18XH103J60RB

# NCU18XH103J60RB







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

