Note: This datasheet may be out of date

Please download the latest datasheet of NFA21SL207X1A45# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL207X1A45%23

"#" indicates a package specification code.

### NFA21SL207X1A45#








< List of part numbers with package codes > NFA21SL207X1A45B NFA21SL207X1A45L



### Appearance & Shape









### **Features**

- 1. Steep insertion loss characteristics
- 2. Suitable for noise suppression in 800MHz or higher frequency
- 3. Size: 2.0x1.25mm
- 4. 4 circuits in one package

Applications
Noise suppression for LCD line



### **Applications**

Other Usage For general



### Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
L	180mm Embossed Tape	4000

1 of 3

### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



NFA21SL207X1A45#

Note: This datasheet may be out of date.

Please download the latest datasheet of NFA21SL207X1A45# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL207X1A45%23

"#" indicates a package specification code.



## **Specifications**

Shape	SMD	
Size Code (in inch)	0805	
Length	2.0mm	
Length Tolerance	±0.1mm	
Width	1.25mm	
Width Tolerance	±0.1mm	
Thickness	0.5mm	
Thickness Tolerance	±0.1mm	
Operating Temperature Range	-55°C to 125°C	
Mass(typ.)	0.007g	
Number of Circuit	4	
Rated Current	100mA	
Rated Voltage	10Vdc	
Withstanding Voltage	30Vdc	
Insulation Resistance(min.)	1000ΜΩ	
Insertion Loss	2dB to 7dB(at Cut-off Frequency),13dB min.(at 500MHz),25dB min.(at 800MHz),25dB min.(at 1000MHz)	
Nominal Cut-off Frequency	200MHz	
Size Code (in mm)	2012	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




# NFA21SL207X1A45#


Note: This datasheet may be out of date.


Please download the latest datasheet of NFA21SL207X1A45# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=NFA21SL207X1A45%23

"#" indicates a package specification code.








**Insertion Loss Characteristics** 

Insertion Loss Characteristics (Main Items)



**Equivalent Circuit** 

3 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

