

FPV1507

Dual conductor high current power inductor



Description

- Dual conductor, two-turn construction
- Magnetically shielded
- 15.1 mm x 8.6 mm footprint surface mount package in a 6.6 mm height
- Ferrite core material
- Halogen free, lead free, RoHS compliant

Applications

- Multi-phase power supplies
- Compatible with Picor® Cool-Power® ZVS Buck-Boost Regulator Family (Picor part number series PI37xx)

Environmental Data

- Storage temperature range (component): -55 °C to +125 °C
- Operating temperature range: -55 °C to +125 °C (ambient plus self-temperature rise)
- Solder reflow temperature: J-STD-020D compliant




Picor® and Cool-Power® are trademarks of Vicor Corporation.

Product Specifications

Part Number ⁵	OCL ¹ (nH) ±10%	I _{rms} ² (A)	I _{sat} ³ (A)	DCR ⁴ (mΩ) @ 20°C	Q minimum reference only
FPV1507-500-R	500	20	40	1.15 ± 0.173	135
FPV1507-650-R	650	20	31	1.15 ± 0.173	135

1. Open Circuit Inductance (OCL) Test Parameters: 1.0 MHz, 0.1 V_{rms}, 0.0 Adc, +25 °C (Pins 1-3, short 2-4)
2. I_{rms}: DC current for an approximate temperature rise of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed 125 °C under worst case operating conditions verified in the end application.
3. I_{sat}: Peak current for approximately 2% rolloff @ +25 °C
4. DCR measured from Pins (1-2) and (3-4)
5. Part Number Definition: FPV1507-xxx-R
FPV1507 = Product code and size
xxx= Inductance value in nH,
-R suffix = RoHS compliant
6. Q test parameters: 1 MHz, 0.1 V_{rms}, +25 °C, (Pins 1-3, short 2-4)
Note: Hipot: 200 Vdc minimum for 2 seconds, 0.1 mA pins (1-2) to (4-3)

Dimensions (mm)



DCR measured from point "A" to point "B"


Part marking: FPV1507-XXX (XXX= inductance value in nH), wwlllyy R=revision level

Soldering surfaces to be coplanar within 0.1 millimeters



Pins 2 & 4 are connected through the PCB trace

Packaging information (mm)

Supplied in tape and reel packaging, 600 parts per 13" diameter reel



Inductance characteristics



Solder reflow profile




Table 1 - Standard SnPb Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 – 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020D

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak		
• Temperature min. (T _{smin})	100°C	150°C
• Temperature max. (T _{smax})	150°C	200°C
• Time (T _{smin} to T _{smax}) (t _s)	60-120 Seconds	60-120 Seconds
Average ramp up rate T _{smax} to T _p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T _L)	183°C	217°C
Time at liquidous (t _L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T _p)*	Table 1	Table 2
Time (t _p)** within 5 °C of the specified classification temperature (T _C)	20 Seconds**	30 Seconds**
Average ramp-down rate (T _p to T _{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
www.eaton.com/elx

© 2016 Eaton
All Rights Reserved
Printed in USA
Publication No. 10347- BU-SB-14810
May 2016



Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)

[FPV1507-500-R](#)