
Spec Sheet

SMD Power Inductors (NR series S type)

NRS4018T4R7MDGJ



Features

- Item Summary
 4.7uH±20%, 1.7A, 4.0x4.0x1.8mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 3500pcs


Products characteristics table

4.7 uH ± 20 %
4.0x4.0
1.7 A
2 A
2.33 A
1.7 A
1.88 A
84 mΩ
70 mΩ
100 kHz
35 MHz
-25 to +125 ℃ (Including-self-generated heat)
± 20 %
Yes
Yes
Reflow

External Dimensions

Dimension L	4.0 ±0.2 mm
Dimension W	4.0 ±0.2 mm
Dimension H	Max 1.8 mm
Dimension e	1.1 ±0.2 mm
Dimension f	2.5 ±0.2 mm

Recommended Land Patterns



2016.12.02

SMD Power Inductors (NR series S type)

NRS4018T4R7MDGJ

Dimension unit : mm unit: inch Length: 4.0 + / - 0.2(0.157 + / - 0.008)Width: 4.0 +/- 0.2 (0.157 + / - 0.008)max.) Height: 1.8 max. (0.071



Inductance: 4.7 (test freq at 0.1MHz) иΗ DC Resistance: 0.07 / 0.084 ohm (typ/max)

Saturation Current: 2,000 mA (max) 1,700 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

