

This document was generated on 03/04/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:0039012161Status:ActiveOverview:Mini-Fit Jr. Power ConnectorDescription:Mini-Fit Jr. Plug Housing, Du Natural	<u>s</u> al Row, 16 Circuits, UL 94V-2, with Panel Mounting Ears,	
Documents: <u>3D Model</u> <u>Drawing (PDF)</u> <u>3D Model (PDF)</u> <u>Product Specification PS-45750-001-001 (PDF)</u> <u>Product Specification PS-5556-001-001 (PDF)</u>	Application Specification 55560001-AS-000 (PDF) Application Specification AS-5557-001-001 (PDF) Packaging Specification PK-5559-001-001 (PDF) Test Summary 55560010-TS-000 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification		EU ELV Not Relevant
CSA UL General	LR19980 E29179	EU RoHS China RoHS Compliant
Product Family Series Application Comments	Crimp Housings <u>5559</u> Power, Wire-to-Board, Wire-to-Wire Current = 13A max. per circuit when header is mated to a receptacle loaded with <u>45750</u> series terminals prime of the 10 AWO wire <u>255 Malayses</u> dust	REACH SVHC Not Contained Per - ECHA_01_2020 (16 January 2020 Halogen-Free Status
Overview Product Name UPC	crimped to 16 AWG wire See Molex product specification PS-45750-001 for additional current derating information. <u>Mini-Fit Jr. Power Connectors</u> Mini-Fit Jr. 800753583979	Low-HalogenFor more information, please visit Contact USChina ROHSGreen ImageELVNot RelevantRoHS PhthalatesNot Contained
Physical Breakaway Circuits (maximum) Color - Resin	No 16 Natural	Search Parts in this Series 5559 Series
Flammability Gender Glow-Wire Capable	94V-2 Plug No	Mates With Mini-Fit Jr. Receptacle Housing <u>5557</u>
Material - Resin Net Weight Number of Rows Packaging Type Panel Mount Pitch - Mating Interface Pitch - Termination Interface	Nylon 4.782/g 2 Bag Yes 4.20mm 4.20mm	Use With Mini-Fit Male Crimp Terminals <u>5558</u> Mini-Fit Plus HCS Crimp Terminals <u>46012</u> Mini-Fit Jr. Grounding Pin <u>30490</u> Mini-Fit Pre-Crimped Leads <u>797580005</u> , <u>797580013</u>
Polarized to Mating Part Stackable Temperature Range - Operating	Yes No -40° to +105°C	
Electrical Current - Maximum per Contact	13.0A	
Material Info Engineering Number	5559-16P	
Reference - Drawing NumbersApplication SpecificationPackaging SpecificationProduct Specification	55560001-AS-000, AS-5557-001-001 PK-5559-001-001 PS-45750-001-001, PS-5556-001-001	

This document was generated on 03/04/2020 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION