



Hand-Held  
Thermal Transfer  
Printing Solutions



PanTher™ LS8E

Cougar™ LS9

<b>Network Component Labels</b>	Pages O.3 – O.4	
<b>Self-Laminating Labels</b>	Page O.5	
<b>Die-Cut Nylon Cloth</b>	Page O.7	
<b>Continuous Nylon Cloth Tape</b>	Page O.7	
<b>Die-Cut Heat Shrink Label Cassettes</b>	Page O.8	Page O.8
<b>Continuous Heat Shrink Label Cassettes</b>	Page O.9	Page O.9
<b>Continuous Tape Cassettes</b>	Page O.10	Page O.10
<b>Ultimate ID® Label Cassettes</b>	Page O.11	Page O.11
<b>Turn-Tell® Labels</b>	Page O.17	
<b>Marker Plates</b>	Page O.18	
<b>Flag Labels</b>	Page O.18	

### P1™ Network Component Label Cassettes for PanTher™ LS8E Hand-Held Thermal Transfer Printer



- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Use for identifying patch panels, faceplates, punchdown blocks and other network systems hardware
- Die-cut labels designed to provide maximum aesthetic quality and appearance
- Available in adhesive polyolefin and non-adhesive polyester materials

Application Description	Typical Application Page	Code
<b>Boxes – Surface Mount, Outlet, Hybrid</b>	G.24	BX
<b>Faceplates</b>	G.2	FP
<b>GP6™ Category 6 Punchdown Blocks</b>	B.72	GP
<b>Jack Modules</b>	B.12	JM

Application Description	Typical Application Page	Code
<b>Punchdown Blocks – 110</b>	B.80	PB
<b>Patch Panels</b>	B.26 – B.27	PP
<b>Racks and Cabinets</b>	L.11	RK
<b>Cable Marker Holder – SLCT</b>	B.90	SL

Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
<b>C061X030FJC</b>	White, adhesive polyolefin label, 500/cassette, Mini-Com® 1-port identifier. Application codes: BX, FP, and PP.	0.61	15.5	0.30	7.6	1	10
<b>C125X030FJC</b>	White, adhesive polyolefin label, 200/cassette, Mini-Com® 2-port identifier. Application codes: BX, FP, and PP.	1.25	31.8	0.30	7.6	1	10
<b>C138X019FJC</b>	White, adhesive polyolefin label, 200/cassette, Mini-Com® Module identifier. Application code: JM.	1.38	35.1	0.19	4.8	1	10
<b>C150X030Y1C</b>	White, non-adhesive polyester label, 75/cassette, Mini-Com® 3-port identifier. Application codes: FP.	1.50	38.1	0.30	7.6	1	10
<b>C188X030FJC</b>	White, adhesive polyolefin label, 150/cassette, Mini-Com® 3-port identifier. Application code: FP.	1.88	47.8	0.30	7.6	1	10
<b>C195X040Y1C</b>	White, non-adhesive polyester label, 100/cassette, single-gang faceplate. Application code: FP.	1.95	49.5	0.40	10.2	1	10
<b>C200X100FJC</b>	White, adhesive polyolefin label, 150/cassette, SLCT bundle marker identifier. Application code: SL, RK.	2.00	50.8	1.00	25.4	1	10
<b>C252X030FJC</b>	White, adhesive polyolefin label, 125/cassette, Mini-Com® 4-port identifier. Application codes: BX, FP, and PP.	2.52	64.0	0.30	7.6	1	10

Order number of cassettes required.

Table continues on next page

**P1™ Network Component Label Cassettes for PanTher™ LS8E Hand-Held Thermal Transfer Printer (continued)**

Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
<b>C261X030FJC</b>	White, adhesive polyolefin label, 125/cassette, Mini-Com® 4-port identifier. Application codes: FP and PP.	2.61	66.3	0.30	7.6	1	10
<b>C261X035Y1C</b>	White, non-adhesive polyester label, 75/cassette, Mini-Com® 4-port identifier. Application codes: FP and PP.	2.61	66.3	0.35	8.9	1	10
<b>C282X030Y1C</b>	White, non-adhesive polyester label, 75/cassette, Mini-Com® 4-port identifier. Application codes: FP and PP.	2.82	71.6	0.30	7.6	1	10
<b>C288X040Y1C</b>	White, non-adhesive polyester label, 75/cassette, double-gang faceplate. Application code: FP.	2.88	73.2	0.40	10.2	1	10
<b>C315X030FJC</b>	White, adhesive polyolefin label, 100/cassette, Mini-Com® 5-port identifier. Application code: FP.	3.15	80.0	0.30	7.6	1	10
<b>C379X030FJC</b>	White, adhesive polyolefin label, 75/cassette, Mini-Com® 6-port identifier. Application code: FP.	3.79	96.3	0.30	7.6	1	10
<b>C390X030Y1C</b>	White, non-adhesive polyester label, 50/cassette, Mini-Com® 6-port identifier. Application code: PP.	3.90	99.1	0.30	7.6	1	10
<b>C750X050Y1C</b>	White, non-adhesive polyester label, 30/cassette, 110 block identifier. Application code: PB.	7.50	190.5	0.50	12.7	1	10
<b>C788X050Y1C</b>	White, non-adhesive polyester label, 30/cassette, GP6™ System identifier. Application code: GP.	7.88	200.2	0.50	12.7	1	10

Order number of cassettes required.