

## This document was generated on 07/11/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0430250208 Active Micro-Fit Connector System Micro-Fit 3.0 Receptacle Hou Inception, Black	sing, Dual Row, 2 Circuits, UL 94V-0, Low-Halogen Since		
	ation 430250000-AS-000 (PDF) tion PK-43025-001-001 (PDF)	<u>Test Summary TS-43045-001-001 (PDF)</u> <u>Test Summary TS-46235-001-001 (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u> <u>Product Literature (PDF)</u>	Series image	e - Reference only
Agency Certificatio	n	1.5.40000	EU ELV	
CSA		LR19980	Not Relevant	
UL		E29179	EU RoHS	China RoHS
General			Compliant	
Product Family		Crimp Housings	REACH SVHC	
Series		<u>43025</u>	Not Contained Per	
3D Viewer		Yes	-ED/88/2018 (15	
Application		Power, Wire-to-Board, Wire-to-Wire	January 2019)	
Comments		Halogen Free/Low Halogen since inception, Halogen	Halogen-Free	
Commonito		Free/Low Halogen since inception	Status	
Overview		Micro-Fit Connector System	Low-Halogen	
Product Literature Order No		987650-5984		n places visit Contact US
Product Name		Micro-Fit 3.0	For more informatio	n, please visit <u>Contact US</u>
UPC		883906114343	China ROHS	Green Image
UPC		003900114343	ELV	Not Relevant
Physical			RoHS Phthalates	Not Contained
Circuits (maximum)		2		Not Contained
Color - Resin		Black		
		94V-0		
Flammability			Search Parts in this Series 43025 Series	
Gender		Receptacle		
Glow-Wire Capable		No	<u></u>	
Keying to Mating Part		None	Mataa With	
Lock to Mating Part		Yes	Mates With Micro-Fit 3.0 Plug Housings <u>43020</u> , Micro-	
Material - Resin		Nylon		
Net Weight		0.261/g	Fit 3.0 Headers <u>43045</u> , Micro-Fit 3.0 Test	
Number of Rows		2	Plug <u>44242</u>	
Packaging Type		Bag		
Panel Mount		No	Use With	
Pitch - Mating Interface		3.00mm	Micro-Fit 3.0 Female Crimp Terminals 43030	
Polarized to Mating Part		Yes	, <u>45773</u> , Micro-Fit RMF Female Crimp	
Stackable		No	Terminals <u>46235</u>	-
Temperature Range	- Operating	-40° to +105°C	j L	
Solder Process Dat	10			
		N/A		
Lead-freeProcess C	apapility	N/A		
Material Info				
Reference - Drawin	a Numbers			
Application Specifica		430250000-45-000		

Application Specification Packaging Specification Sales Drawing Test Summary

430250000-AS-000 PK-43025-001-001 SD-43025-001-001 TS-43045-001-001, TS-46235-001-001

## This document was generated on 07/11/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION