



COTS Micro-D Solder Cup Plastic Shell

Solder Cup Micro-D Plastic Connectors are ideal for applications where cost is a prime consideration. The high temperature LCP insulator resists damage from soldering heat.

- #26 to #30 AWG Wire Accomodation
- Economical Plastic Body, Non-Environmental
- 9 Through 51 Contacts
- Precision Machined Solder Cups



Note: Micro-D plastic connectors are not intermatable with metal shell connectors.

RELATED INFORMATION

Performance Specifications	IBC*
Materials and Finishes	IBC*
Contact Arrangements	7-8
Panel Cutouts, Mounting Dimensions	9
Standard Dimensions	10
Jacking Hardware Kits	C-3,4

* Available on the Inside Back Cover Fold-Out

HOW TO ORDER

Conn. Series	Housing Material Table I*	No. of Contacts	Contact Type	Termination	Hardware Table V*
MWD	L – LCP (Liquid Crystal Polymer)	9	P – Pin, #26 AWG (Standard)	S - Solder Cup	B
		15			P
		21	S – Socket, #26 AWG (Standard)		L
		25			K
		31	N – Pin, #24 AWG		M
		37	T – Socket, #24 AWG		S
		51			M1
					S1
					F
					R

Sample Part Number:

MWD L — 37 P S B

* SEE INSIDE BACK COVER FOLD-OUT FOR COMPLETE INFORMATION