

# Products & Applications: Fume Extraction

## **BVX-200 Series Fume Extraction Systems**

## Two Station Design for Dynamic Fume Extraction

The BVX-200 Series Fume Extraction Systems are revolutionary two-arm units that combine powerful fan performance with efficient filtration, quiet operation and complete portability. They can be placed under or next to the bench-top and fitted with either two 50mm (2") diameter BVX arms or one 63mm (2.5") diameter Omniflex arm.

Using the proven fan motor of the BVX-100 Series Fume Extraction Systems, the BVX-200 Series Fume Extractions Systems add a proprietary one-stage impeller design that doubles the total free-blowing airflow.

The result is a maximum free-blowing airflow of 250m3/h (150cfm), with a maximum suction force of 850 Pa (3.5"WC). This suction force provides ample capability in reserve to handle any clogging that may occur during the normal life of the filter. It is, in fact, the suction rating for this unit is one of the best in its class offered for such compact and portable systems.

The BVX-201 Fume Extraction System is designed mainly for solder fumes and incorporates both pre- and main-filters which can be changed independently to maximize the working life of each filter and lower the total cost of ownership. The main filter has a HEPA efficiency of 99.97% at 0.3 micron, plus an activated carbon filter to remove additional gases. For applications that require a high capacity of gas filtration, such as cleaning with solvents or conformal coatings, the BVX-203 Fume Extraction System features a deep-bed gas filter.



Technical Specifications

Static Pressure (suction force): 850 Pa (3.5" WC) Fan Capacity: 250m3/h (150 cfm) Flow Rate (with filter): 2 x 75m3/h (450 cfm) Air Inlets/Number of Stations: 2 HEPA Efficiency: 99.97% at 0.3 micron Noise Level: < 55 db A Dimensions (W x D x H): 508mm x 254mm x 388mm (20" x 15" x 15.3") Weight: 9kg (20 lbs) Voltage : 100-240 VAC Frequency : 50-60 Hz Power : 85 watt Certification : UL, CSA, CE

#### Quick Links

- » BVX-200 Series Fume Extraction Systems
- » BVX-200 Series Part Numbers

### **BVX-200 Series Part Numbers**

#### **SYSTEMS**

- ITEM PART NO.
- BVX-201-KIT Filter unit with 2 flexible arms, 1.2m long, Pre-HEPA-Gas
- BVX-201 Filter unit for 2 stations, Pre-HEPA-Gas
- BVX-203 Filter unit for 2 stations, Pre-Deep Bed Gas

FILTERS

- ITEM PART NO.
- FP-BVX200 Pre Filter (Pack of 5)
- FM-BVX200 Main Filter HEPA Carbon
- FG-BVX200 Deep Bed Gas Filter

#### ACCESSORIES

- ITEM PART NO.
- BVX-ARM-K1 1 BVX arm 710mm (28") long with 1.8m (6') long hose and table bracket with C-clamps
- BVX-ARM Arm flexible ESD safe, 710mm (28") long
- BVX-ARML Arm flexible ESD safe, 1.2m (48") long
- BVX-TB01 Table bracket with 2 C-clamps
- BVX-CH01 Connection hose, 50mm (2") diameter, 1.8m (6') long
- BVX-CH02 Connection hose, 50mm (2") diameter, 3.6m (12') long





BVX-201-KIT

BVX-201 With 2 x BVX-ARM-K1

BVX-ARM-K1

A DOVER COMPANY

© 2005 OK International. All rights reserved. Home | Code of Business Conduct | Terms & Conditions | Privacy Policy / Legal | Site Map Soldering/Desoldering Systems | Fluid Dispensing Systems BGA Rework Technology | Fume Extraction | Soldering Irons | Metcal MX | Soldering Tips