



Today's work and lifestyles require us to communicate anytime, anywhere whether on the move or sitting still. Bluetooth and 802.11 standards make wireless connections to computer networks and other devices possible, while at the same time enabling freedom of movement.

Laird Connectivity's practical and rugged external wireless device antennas are designed to fit into the portable devices used in office, industrial and home environments. The antennas feature flexible elements and many are ½ wave coaxial dipole design for reduced ground dependence and improved performance.

### FEATURES AND BENEFITS

- Injection-molded ¼ wave flexible cable antenna
- High durability, high efficiency
- Textured finish with strain-relief base
- Available in various standard connectors
- An original Tuf Duck antenna

### APPLICATIONS

- For Bluetooth and IEEE 802.11b/g devices

### SPECIFICATIONS

Model Name	EXCxxx
Operating Frequency (MHz)	UHF Trunking/Cellular
VSWR – Max	1.5:1
Nominal Impedance (Ohms)	50
Power Handling (W)	50
Polarization	Vertical
Drop Test (M)	1
Operating Temperature – °C (°F)	-40 to +85°C (-40 to +185°F)

### CONFIGURATION

PART NUMBER	FREQUENCY BAND	CONNECTOR	AVERAGE LENGTH
EXC340	336-343 MHz	BNX	20.32 cm (8.0 in.)
EXC400	400-420 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	17.15 – 17.8 cm (6.75 – 7.0 in.)
EXC410		SMI	
EXC420	420-450 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	17.15 – 17.8 cm (6.75 – 7.0 in.)
EXC450	450-470 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	16.23 – 17.53 cm (6.39 – 6.9 in.)
EXC470	470-512 MHz	BN, BNX, KR, MD, MX, MXI, SF, SFU, SM, SMV, TN, TNX	15.57 – 17.02 cm (6.13 – 6.7 in.)
EXC806	806-866 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	9.4 – 11.68 cm (3.7 – 4.6 in.)
EXC868		SM	8.9 cm (3.5 in.)
EXC902	902-960 MHz	BN, BNX, KR, MD, MX, SF, SFU, SM, SMV, TN, TNX	8.9 – 9.27 cm (3.5 – 3.65 in.)
EXC1000	1000 MHz	BN	8.38 (3.3 in.)

**Note:** Order by antenna model, frequency, and connector (for example: EXC450MX). The length of each antenna varies according to the chosen connector.



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2019 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

sales@lairdconnect.com  
support@lairdconnect.com  
www.lairdconnect.com



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[EXC450BN](#) [EXC450SM](#) [EXC450TN](#) [EXC450TNX](#) [EXD470MX](#) [EXC340BNX](#)