


CC7V-T1A

Tuning Fork Crystal 32.768 kHz



DIMENSIONS



APPLICATIONS

IoT
 Metering
 Industrial
 Automotive
 Health Care
 Wearables, Portables

DESCRIPTION

The CC7V-T1A is a low frequency SMD Quartz Crystal Unit that incorporates a tuning fork Quartz Crystal Resonator. It operates under vacuum in a hermetically sealed ceramic package with ceramic lid.

FEATURES

Outstanding hermetic sealing with gold-tin preform.
 High stability and low aging guaranteed by hermetic sealing.
 Available for extended operating temperature range.
 Small size, low profile, lightweight (12.5 mg).
 High shock and vibration resistant.
 100% Pb-free, RoHS-compliant.
 Automotive qualification according to AEC-Q200 available.

ELECTRICAL CHARACTERISTICS AT 25°C

Standard Frequency	¹⁾ F _L	32.768	kHz
Load capacitance	²⁾ C _L	6.0 / 7.0 / 9.0 / 12.5	pF
Frequency tolerance	³⁾ ΔF/F	±20	ppm
	ΔF/F	±100	ppm
Series resistance typ./max.	R _S	50 / 70	kΩ
Motional capacitance typ.	C ₁	3.7	fF
Static capacitance typ.	C ₀	1.2	pF
Drive level max.	P	1.0	μW
Insulation resistance min.	R _i	500	MΩ
Aging first year max.	ΔF/F	±3	ppm
Turnover temperature	T ₀	25 ±5	°C
Frequency vs. temperature	ΔF/F ₀	-0.035 ppm/°C ² (T - T ₀) ² ±10%	ppm

- 1) Other frequencies on request.
 2) Other load capacitances on request.
 3) Tighter frequency tolerances on request.

STANDARD FREQUENCIES

Frequency
32.768 kHz
Other frequencies on request

ENVIRONMENTAL CHARACTERISTICS

		Conditions	Max. Dev.
Storage temperature range		-55 to +125°C	
TA Operating temperature range		-40 to +85°C	
TB Extended oper. temp. range		-40 to +125°C	
TC Extended oper. temp. range		-55 to +125°C	
Shock resistance	ΔF/F	5000 g, 0.3 ms, ½ sine	±5 ppm
Vibration resistance	ΔF/F	20 g / 10–2000 Hz	±5 ppm

TERMINATIONS AND PROCESSING

Type	Termination	Processing
CC7V-T1A	Au flashed pads	IPC/JEDEC J-STD-020C 260°C / 20 - 40 s

ORDERING INFORMATION

<p style="text-align: center;">C C 7 V - T 1 A 32.768 kHz 12.5 pF ±20 ppm TA QC</p> <p>Ceramic package _____</p> <p>Ceramic lid _____</p> <p>Package size _____ 7 = 3.2 x 1.5 x 0.90 mm</p> <p>Tuning fork _____</p> <p>SMT Package _____</p> <p>Au flashed pads _____</p> <p>2 pads _____</p>	<p>Frequency F_L _____</p> <p>Load capacitance C_L _____ 6.0 pF 7.0 pF 9.0 pF 12.5 pF Other C_L on request</p> <p>Frequency tolerance _____ ±20 ppm ±100 ppm Tighter freq. tolerances on request</p> <p>Temperature range _____ TA = -40 to +85°C (Standard) TB = -40 to +125°C TC = -55 to +125°C</p> <p>Qualification _____ QC = Commercial Grade (Standard) QA = Automotive Grade AEC-Q200 QM = Medical Grade</p>
--	--

A unique part number will be generated for each product specification, i.e:	
20xxxx-MG01	1'000 pcs (in 12 mm tape on 7" reel)
20xxxx-MG03	3'000 pcs (in 12 mm tape on 7" reel)
20xxxx-PG14	14'000 pcs (in 12 mm tape on 13" reel)

All specifications subject to change without notice.



Micro Crystal AG
Muehlestrasse 14
CH-2540 Grenchen
Switzerland

Phone +41 32 655 82 82
sales@microcrystal.com
www.microcrystal.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Crystal:

[CC7V-T1A-32.768kHz-12.5pF-10PPM-TA-QC](#) [CC7V-T1A-32.768kHz-9pF-20PPM-TC-QC](#) [CC7V-T1A-32.768k-9pF-100PPM-TC-QA](#) [CC7V-T1A-32.768kHz-12.5pF-20PPM-TA-QC](#) [CC7V-T1A-100.000kHz-9pF-100PPM-TA-QC](#) [CC7V-T1A-32.768k-12.5pF-20PPM-TC-QA](#) [CC7V-T1A-32.768k-7pF-20PPM-TB-QA](#) [CC7V-T1A-32.768k-9pF-20PPM-TA-QA](#) [CC7V-T1A-32.768k-12.5pF-20PPM-TB-QA](#) [CC7V-T1A-32.768kHz-7pF-100PPM-TA-QC](#) [CC7V-T1A-32.768k-9pF-20PPM-TC-QA](#) [CC7V-T1A-32.768kHz-7pF-20PPM-TA-QC](#) [CC7V-T1A-32.768kHz-9pF-100PPM-TA-QC](#) [CC7V-T1A-32.768kHz-7pF-20PPM-TB-QC](#) [CC7V-T1A-32.768k-9pF-20PPM-TB-QA](#) [CC7V-T1A-32.768k-12.5pF-20PPM-TA-QA](#) [CC7V-T1A-32.768kHz-12.5pF-20PPM-TC-QC](#) [CC7V-T1A-32.768kHz-12.5pF-100PPM-TA-QC](#) [CC7V-T1A-32.768kHz-9pF-10PPM-TA-QC](#) [CC7V-T1A-32.768kHz-9pF-20PPM-TA-QC](#) [CC7V-T1A-32.768kHz-7pF-10PPM-TA-QC](#) [CC7V-T1A-32.768kHz-9pF-10PPM-TA-QC T3](#)