Data Sheet

HUBER+SUHNER

Coaxial PCB Connector 85_BNC-50-0-1/133_N

Description

Right angle PCB jack

Interface Standards IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data Impedance Interface frequency max.	50 Ω 4 GHz
Mechanical Data Board mounting type Weight	through holes 0.0187 kg
Environmental Data Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-65 °C to 165 °C compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00070952
Catalogue drawing	DCA-00012658
Mounting hole	DOU-00012084

Ordering Information

Single package

85_BNC-50-0-1/133_NE

Remarks

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 85_BNC-50-0-1/133_NE