













	φ	0.750 +0.010 [19,05 +0.25]
$1.260^{\pm0.005} \\ [32,00^{\pm0.12}]$		1.660 [42,16]
0.200 [5,08]	Ф	R 0.078 ±0.005 [1,98 ±0,12]

PANEL CUTOUT DETAIL



ANSI SERIES TRIP	TIGHTENING TORQUE SPECIFICATIONS		
LINE o	THREAD SIZE	TORQUE	
(#6-32 & M3 MOUNTING HARDWARE	7-9- IN-LBS [0.8-1.0 NM]	
	#8-32 & M4 THREAD TERMINAL SCREW	12-15 IN-LBS [1.4-1.7 NM]	MA PR

PROPRIETARY NOTICE NOTICE TO ALL PERSONS RECEIVING THIS DRAWING. THIS DOCUMENT IS THE PROPERTY OF CARLING TECHNOLOGIES, INC. AND IS NOT TO BE DISCLOSED, REPRODUCED IN WHOLE OR IN PART OR USED FOR MANUFACTURING PURPOSES BY ANYONE WITHOUT THE CONSENT OF CARLING TECHNOLOGIES, INC.

DISCLAIMER

MANUFACTURER RESERVES THE RIGHT TO CHANGE PRODUCT SPECIFICATIONS WITHOUT PRIOR NOTICE.

DO NOT SCALE DRAWING			
UNLESS OTHERWISE SPECIFIED			
DIMENSIONS: IN [MM]			
TOLERANCES: ± .020 [0.51]			
DRAWING FILE NO.	SIZE		
AC1-B0-34-610-1G1-C	С		

PRODUCT SERIES: A-SERIES C.B. SHEET 1 OF 1

CIRCUIT_BREAKER

			_
CIRCUIT SCHEMATIC	TABLE A TIGHTENING TORQUE SPECIFICATIONS		
ANSI SERIES TRIP			
LINE o	THREAD SIZE	TORQUE	
c¦	#6-32 & M3 MOUNTING HARDWARE	7-9- IN-LBS [0.8-1.0 NM]	
	#8-32 & M4 THREAD TERMINAL SCREW	12-15 IN-LBS [1.4-1.7 NM]	MA PF
LOAD	#10-32 & M5 THREAD TERMINAL SCREW	15-20 IN-LBS [1.7-2.3 NM]	