



# Dismantling Knife 1000V

- With protection cap
- With fixed blade
- With straight, half-round polished blade for plastic cables
- Ergonomically designed safety handle made of tough elastic, impact-resistant plastic
- Insulation according to DIN EN/IEC 60900
- Blade made of stainless steel, hardened

# SKU: 2041





## **General Information**

### Cable Knives

The blades of these knives are made of hardened stainless steel to guarantee clean cuts through wires and cables. The ergonomically designed safety handles fit snugly in the hand and, thanks to the tough, elastic, impact-resistant plastic used for the protective cover and handles, the risk of injury and strain is minimised.



### Better safe than sorry.

Electricians put their faith in their tools daily. Electricity is always a potential hazard. Whether they are cutting cables to size, fitting socket outlets or configuring switch cabinets, they need tools they can rely on without fail. When an electrician picks up a set of VDE tools made by NWS, he or she is handling quality tools subjected to stringent testing for practical, hands-on applications in electrical jobs. This is, after all, what professional working, health & safety are all about.



Safety testing method according to IEC 60900

• Visual check and check of measurements: single check of the lettering on the basis tool as well as on the insulation.

• Check of resistance under hot and cold conditions: under normal temperatures of the surroundings (23° C) as well as under low temperatures (-25° C) on three different positions easy to hurt.

• Single voltage check: check of the electrical insulating characteristics by putting on a 10 KV voltage in a water bath for three minutes and measuring the deflecting electricity.

• Pressure check - check of puncture: storage of tools in a warming box for 2 hours at the temperature of 70° C putting on a 5 KV Voltage for three minutes and raising a power of 20 N on the insulation.

• Check of the adhesive power of the insulation: storage of tools in a warming box for 168 h at a temperature of

70° C raising a power of 500 N for three minutes on the area between the conductive part and the insulation.

• Check of fire risk: raising a flame on the insulation for 10 seconds.



echnical Data		
204	1	
41	Length - mm	185
٩F	Length - in	7
<b>4</b>	Cutting edge length - mm	35
-	Handle length - mm	150
	Design	<u>⊗ 1000 v</u>
52	Weight - g	95
9	Packing unit	1
	Barcode	40 03758 20410 8