


# D SUB HD FE CRIMP SHELL 44P



Part number	09 56 300 4701
Specification	D SUB HD FE CRIMP SHELL 44P
HARTING eCatalogue	https://b2b.harting.com/09563004701

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	D-Sub
Identification	High Density
Element	Connector

#### Version

Termination method	Crimp termination
Gender	Female
Size	D-Sub 3
Number of contacts	44
Locking type	Fixing flange with feed through hole Ø 3.1 mm

#### Technical characteristics

Conductor cross-section	0.14 0.25 mm²
Conductor cross-section	AWG 26 AWG 24
Wire outer diameter	≤1.38 mm
Clearance distance	≥1 mm
Creepage distance	≥1 mm
Insulation resistance	> 5 x 10 <sup>9</sup> Ω
Limiting temperature	-40 +85 °C
Withdrawal force	≤9.8 N
Test voltage U <sub>r.m.s.</sub>	1 kV
Isolation group	IIIa (175 ≤ CTI < 400)



#### Technical characteristics

	Hot plugging	No	
--	--------------	----	--

## Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: steel, nickel plated
Colour (insert)	Black
Material (contacts)	Copper alloy
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

## Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

#### Commercial data

Packaging size	100
Net weight	8.58 g
Country of origin	China
European customs tariff number	85366990
eCl@ss	27440214 D-Sub coupler

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING: 09563004701