



POK1.1206.2P.B


SMD platinum sensor

For the automatic assembling on PCBs

Benefits & Characteristics

- Excellent long-term stability
- Low self-heating
- Fast response time


Illustration¹⁾



Technical Data

Operating temperature range:	-50 °C to +150 °C	
Nominal resistance:	100 Ω at 0 °C	
Characteristics curve:	3850 ppm/K	
Long-term stability:	< 0.04 % at 1000 h at 130 °C	
Tolerance class (dependent on temperature range):	IEC 60751 F0.3	B (IST AG reference)
Connection:	tin-coated (96.5Sn/3Ag/0.5Cu), LMP lead-free, (reflow soldering)	
Dimensions:	2.9 / 0.35 / 2.2 x 1.5 / 1.35 x 0.45	
Tolerance:	±0.2 mm (H ±0.15)	
Solderability:	235 °C ≤ 8 s (DIN IEC 68 T2-20, Ta Meth. 1)	
Resistance to soldering heat: ¹⁾ <small>1) The soldering process can influence accuracy</small>	260 °C 10 s (DIN IEC 68 T2-20, Ta Meth. 1A)	
Recommended applied current: ²⁾ <small>2) Self-heating must be considered</small>	1 mA at 100 Ω	
Packaging:	Packed in bags (< 100 pcs)	

Product Photo





Order Information

Description:	Item number:	Former main reference:
P0K1.1206.2P.B	100602	010.01132

Additional Documents

Application Note:	Document name:
	ATP_E



Innovative Sensor Technology IST AG, Stegrütistrasse 14, 9642 Ebnat-Kappel, Switzerland
Phone: +41 71 992 01 00 | Fax: +41 71 992 01 99 | Email: info@ist-ag.com | www.ist-ag.com

All mechanical dimensions are valid at 25 °C ambient temperature, if not differently indicated • All data except the mechanical dimensions only have information purposes and are not to be understood as assured characteristics • Technical changes without previous announcement as well as mistakes reserved • The information on this data sheet was examined carefully and will be accepted as correct; No liability in case of mistakes • Load with extreme values during a longer period can affect the reliability • The material contained herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner • Typing errors and mistakes reserved • Product specifications are subject to change without notice • All rights reserved