

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 24_QMA-50-2-3/133_N



Description

Straight panel bulkhead cable jack, flange mount

Interface standards
QMA QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0043 kg

Environmental Data

Operating Temperature -40 °C to 85 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Gasket	MVQ (Silicone Rubber)
Fastening nut	Brass
Washer	Bronze
Crimp ferrule	Copper

Surface Plating

SUCOPRO Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009505
Catalogue drawing	DCA-00008995
Assembly instruction	DOC-0000179456
Mounting hole	DOU-00008748

Ordering Information

Single package	24_QMA-50-2-3/133_NE
Bulk 100 pcs package	24_QMA-50-2-3/133_NH

Additional Information

Suitable cables RG_316_U, ENVIROFLEX_316, RG_188_A/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions