BAXTER

COMFORT AND INGENUITY

BAXTER, the alternative to the TRACKER model, offers total comfort thanks to its highly wraparound frame. With its waterproof foam and ingenious system for attaching the strap, BAXTER offers effective protection against sprays of solids and liquids, and against dust. BAXTER will soon be available in the RX range.







BAXPSI



BAXPSF



BAXCSP





- **+** INCREASED PROTECTION
- **+** WRAP-AROUND FRAME
- **+** WATERPROOF FOAM AND REMOVABLE STRAP
- **+** COATING ♦ PLATINUM (+**P**)



BAXTER

COMFORT AND INGENUITY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
	Clear	BAXPSI	2C-1,2 😭 1 BT KN €€	≅ EN166 FT C€	Anti-scratch /Anti-fog (⁺₽)
BAXTER	Smoke	BAXPSF	5-3,1 😭 1 BT KN €€	≅ EN166 FT C€	Anti-scratch /Anti-fog (⁺₽)
	b csp	BAXCSP	5-1,4 😭 1 BT KN €€	≅ EN166 FT C€	Anti-scratch /Anti-fog (⁺₽)
Strap version	With strap & foam	-	-		-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- **B.** Impact à moyenne énergie, résiste à une bille de 6 mm et de 0,86 g à 120 m/s.

Others symbols:

- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)

TECHNOLOGY

∠CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM coating that sustainably combats fogging.

\$PL∧TINUM

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- 4. Large dust particles > 5 microns.
- **5.** Gas and fine dust particles < 5 microns.
- **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- **B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE							
	BAXPSI	BAXPSF	BAXCSP				
Individual plastic bag	3660740007744	3660740007751	3660740007768				
10 safety spec- tacles per inner box			3660740107765				
240 safety spectacles per outer pack	3660740207748	3660740207755	3660740207762				

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
FRAME	PC			
TEMPLES	PC			
STRAP	Nylones, Polyester, Fiber			
FOAM	PC			









DIN INSPEC

11/12/2015

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

