F204 A-63/0,3

General Information

Extended Product Type:	F204 A-63/0,3
Product ID:	2CSF204101R3630
EAN:	8012542783909
Catalog Description:	F204 A-63/0,3 Residual Current Dev.
Long Description:	The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Residual Current Devices RCDs » Residual Current Devices RCDs

Ordering EAN:	8012542783909
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Dimensions	
Product Net Width:	0.070 m
Product Net Height:	0.085 m
Product Net Depth:	0.069 m
Product Net Weight:	0.360 kg
Container Information	
Package Level 1 Units:	1 piece
Package Level 1 Width:	0.082 m
Package Level 1 Height:	0.078 m
Package Level 1 Length:	0.096 m
Package Level 1 Gross Weight:	0.403 kg
Package Level 1 EAN:	8012542783909
Package Level 2 Units:	3 piece
Package Level 2 Gross Weight:	1.125 kg
Environmental	
Environmental RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q
RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q
RoHS Status: Additional Information	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q Level 0 - Information enabled
RoHS Status: Additional Information IIT Publishing Status:	
RoHS Status: Additional Information IIT Publishing Status: Number of Poles:	Level 0 - Information enabled
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic:	Level 0 - Information enabled 4
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals:	Level 0 - Information enabled 4 Instantaneous
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss:	Level 0 - Information enabled 4 Instantaneous Right
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Name:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Name: Rated Current (I _n):	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Rated Current (I _n): Rated Residual Current:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r):	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards: Type of Residual Current:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards: Type of Residual Current: Certificates and Declarations (I	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type Document Number)
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards: Type of Residual Current: Certificates and Declarations (I	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards: Type of Residual Current: Certificates and Declarations (I Declaration of Conformity - CE:	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type Document Number)
RoHS Status: Additional Information IIT Publishing Status: Number of Poles: Operating Characteristic: Position of Neutral Terminals: Power Loss: Product Main Type: Product Name: Rated Current (I _n): Rated Residual Current: Rated Voltage (U _r): Standards: Type of Residual Current: Certificates and Declarations (I Declaration of Conformity - CE: Classifications	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type Document Number)
	Level 0 - Information enabled 4 Instantaneous Right Per Pole 4.4 W F200 Residual Current Device 63 A 300 mA 230/400 V IEC EN 61008 A type Document Number) ITSCE116F200