

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0039014056		
Status: Active		
AUTIC	octoro	
	ngle Row, 5 Circuits, UL 94V-2, without Panel Mounting	
Ears, Natural	igle Row, 5 Circuits, DE 94V-2, without Parlet Mounting	
Documents:		
<u>3D Model (PDF)</u>	Application Specification AS-5557-001-001 (PDF)	
Drawing (PDF)	Packaging Specification PK-5559-003-001 (PDF)	
3D Model	Test Summary 55560010-TS-000 (PDF)	
Product Specification PS-45750-001-001 (PDF)	Test Summary TS-5556-002-001 (PDF)	Series image - Reference only
Product Specification PS-5556-001-001 (PDF)	RoHS Certificate of Compliance (PDF)	
Application Specification 55560001-AS-000 (PDF)		EU ELV
		Not Relevant
Agency Certification		
CSA	LR19980	EU RoHS China RoHS
UL	E29179	Compliant
General		REACH SVHC
Product Family	Crimp Housings	Not Contained Per - D(2021)4569-DC (8
Series	5559	July 2021)
Application	Power, Wire-to-Board, Wire-to-Wire	Halogen-Free
Comments	Current = 13A max. per circuit when header is mated	Status
	to a receptacle loaded with <u>45750</u> series terminals	Low-Halogen
	crimped to 16 AWG wire. See Molex product	For more information, please visit Contact US
	specification PS-45750-001 for additional current	
	derating information.	China ROHS Green Image
Overview	Mini-Fit Family Power Connectors	ELV Not Relevant
Product Name	Mini-Fit Jr.	RoHS Phthalates Not Contained
UPC	800753760318	
Physical		
Breakaway	No	Search Parts in this Series
Circuits (maximum)	5	<u>5559</u> Series
Color - Resin	Natural	
Flammability	94V-2	Mates With
Gender	Plug	Mini-Fit Jr. Receptacle Housing <u>39014050</u> br>Mini-Fit TPA2 Cable Assembly 145135
Glow-Wire Capable	No	<pre><bi><bi><bi><bi><bi><bi><bi><bi><bi><bi< td=""></bi<></bi></bi></bi></bi></bi></bi></bi></bi></bi></pre>
Keying to Mating Part Lock to Mating Part	None Yes	
Material - Resin	Nylon	Use With
Net Weight	1.800/g	Mini-Fit Male Crimp Terminals <u>5558</u>
Number of Rows	1	46012 br>Mini-Fit Jr. Grounding Pin <u>30490</u>
Packaging Type	Bag	<pre> <br <br="" c<="" column="" td=""/></pre>
Panel Mount	No	, 797580013
Pitch - Mating Interface	4.20mm	
Pitch - Termination Interface	4.20mm	
Polarized to Mating Part	Yes	
Stackable	No 10° to 1105°C	
Temperature Range - Operating	-40° to +105°C	
Electrical		
Current - Maximum per Contact	13.0A	
Solder Process Data		
Lead-freeProcess Capability	N/A	
Material Info		

5559-05P3

Reference - Drawing Numbers Application Specification Packaging Specification Product Specification Sales Drawing Test Summary

55560001-AS-000, AS-5557-001-001 PK-5559-003-001 PS-45750-001-001, PS-5556-001-001 55590002-SD-000 55560010-TS-000, TS-5556-002-001

This document was generated on 08/25/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION