



600W SURFACE MOUNT TRANSIENT VOLTAGE SUPPRESSORS

SMBJXXX



DO-214AA (SMB)



DO-214AA(SMB)
Surface Mount
Plastic Package
RoHS compliant

FEATURES:

1. Peak power dissipation 600W @ 10 x 1000 μ s pulse
2. Low profile package
3. Excellent clamping capability
4. Glass passivated junction
5. Fast response time: typically less than 1 pS from 0 Volts to BV_{min}
6. IEC 61000-4-2 ESD 30KV(Air), 30KV(Contact)
7. ESD protection of data lines in accordance with IEC 61000-4-2
8. EFT protection of data lines in accordance with IEC 61000-4-4
9. Lead-free finish
10. This device is available in AEC-Q101 complaint also.
11. Note: For AEC-Q101 compliant products, please suffix - AQ in the part number while ordering

ABSOLUTE MAXIMUM RATINGS (Ta = 25 °C Unless otherwise specified)

PARAMETER	SYMBOL	VALUE	UNIT
Peak Pulse Power Dissipation on 10/1000 μ s Waveform ^{1,2} (FIG.1)	P_{PPM}	Min 600	W
Power Dissipation on Infinite Heat Sink at $T_L = 50^\circ\text{C}$	P_D	5	W
Peak Pulse Current of on 10/1000 μ s Waveform ¹ (FIG.3)	I_{PPM}	See table 1	A
Peak Forward Surge Current, 8.3ms Single Half Sine-Wave (Note 2, 3)	I_{FSM}	100	A
Operating Junction Temperature Range	T_J	-55 to +150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150	$^\circ\text{C}$
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	100	$^\circ\text{C/W}$

Note:

1. Non-repetitive current pulse, per Fig.3 and derated above $T_A = 25^\circ\text{C}$ per Fig.2.
2. Mounted on 5.0x5.0mm² (0.03mm thick) Copper Pads to each terminal.
3. Measured on 8.3ms single half sine-wave, or equivalent square wave, for Unidirectional device only



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



ELECTRICAL CHARACTERISTICS at (Ta = 25 °C Unless otherwise specified)

TYPE NUMBER		MARKING		REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE MIN. @I _T	BREAKDOWN VOLTAGE MAX. @I _T	TEST CURRENT	MAXIMUM CLAMPING VOLTAGE @I _{PP}	PEAK PULSE CURRENT	REVERSE LEAKAGE @V _{RMW}
(UNI)	(BI)	UNI	BI	V _{RMW} (V)	V _{BR MIN} (V)	V _{BR MAX} (V)	I _T (mA)	V _C (V)	I _{PP} (A)	I _R (μA)
SMBJ5.0A	SMBJ5.0CA	KE	AE	5.0	6.40	7.00	10	9.20	65.30	800
SMBJ6.0A	SMBJ6.0CA	KG	AG	6.0	6.67	7.37	10	10.30	58.30	800
SMBJ6.5A	SMBJ6.5CA	KK	AK	6.5	7.22	7.98	10	11.20	53.60	500
SMBJ7.0A	SMBJ7.0CA	KM	AM	7.0	7.78	8.60	10	12.00	50.00	200
SMBJ7.5A	SMBJ7.5CA	KP	AP	7.5	8.33	9.21	1	12.90	46.60	100
SMBJ8.0A	SMBJ8.0CA	KR	AR	8.0	8.89	9.83	1	13.60	44.20	50
SMBJ8.5A	SMBJ8.5CA	KT	AT	8.5	9.44	10.40	1	14.40	41.70	20
SMBJ9.0A	SMBJ9.0CA	KV	AV	9.0	10.00	11.10	1	15.40	39.00	10
SMBJ10A	SMBJ10CA	KX	AX	10.0	11.10	12.30	1	17.00	35.30	5
SMBJ11A	SMBJ11CA	KZ	AZ	11.0	12.20	13.50	1	18.20	33.00	1
SMBJ12A	SMBJ12CA	LE	BE	12.0	13.30	14.70	1	19.90	30.20	1
SMBJ13A	SMBJ13CA	LG	BG	13.0	14.40	15.90	1	21.50	27.90	1
SMBJ14A	SMBJ14CA	LK	BK	14.0	15.60	17.20	1	23.20	25.90	1
SMBJ15A	SMBJ15CA	LM	BM	15.0	16.70	18.50	1	24.40	24.60	1
SMBJ16A	SMBJ16CA	LP	BP	16.0	17.80	19.70	1	26.00	23.10	1
SMBJ17A	SMBJ17CA	LR	BR	17.0	18.90	20.90	1	27.60	21.80	1
SMBJ18A	SMBJ18CA	LT	BT	18.0	20.00	22.10	1	29.20	20.60	1
SMBJ20A	SMBJ20CA	LV	BV	20.0	22.20	24.50	1	32.40	18.60	1
SMBJ22A	SMBJ22CA	LX	BX	22.0	24.40	26.90	1	35.50	16.90	1
SMBJ24A	SMBJ24CA	LZ	BZ	24.0	26.70	29.50	1	38.90	15.50	1
SMBJ26A	SMBJ26CA	ME	CE	26.0	28.90	31.90	1	42.10	14.30	1
SMBJ28A	SMBJ28CA	MG	CG	28.0	31.10	34.40	1	45.40	13.30	1
SMBJ30A	SMBJ30CA	MK	CK	30.0	33.30	36.80	1	48.40	12.40	1
SMBJ33A	SMBJ33CA	MM	CM	33.0	36.70	40.60	1	53.30	11.30	1
SMBJ36A	SMBJ36CA	MP	CP	36.0	40.00	44.20	1	58.10	10.40	1
SMBJ40A	SMBJ40CA	MR	CR	40.0	44.40	49.10	1	64.50	9.30	1
SMBJ43A	SMBJ43CA	MT	CT	43.0	47.80	52.80	1	69.40	8.70	1
SMBJ45A	SMBJ45CA	MV	CV	45.0	50.00	55.30	1	72.70	8.30	1
SMBJ48A	SMBJ48CA	MX	CX	48.0	53.30	58.90	1	77.40	7.80	1
SMBJ51A	SMBJ51CA	MZ	CZ	51.0	56.70	62.70	1	82.40	7.30	1
SMBJ54A	SMBJ54CA	NE	DE	54.0	60.00	66.30	1	87.10	6.90	1
SMBJ58A	SMBJ58CA	NG	DG	58.0	64.40	71.20	1	93.60	6.50	1
SMBJ60A	SMBJ60CA	NK	DK	60.0	66.70	73.70	1	96.80	6.20	1
SMBJ64A	SMBJ64CA	NM	DM	64.0	71.10	78.60	1	103.00	5.90	1

SMBJXXX

Rev02_14042021ESW


ELECTRICAL CHARACTERISTICS at (Ta = 25 °C Unless otherwise specified)

TYPE NUMBER		MARKING		REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE MIN. @I _T	BREAKDOWN VOLTAGE MAX. @I _T	TEST CURRENT	MAXIMUM CLAMPING VOLTAGE @I _{PP}	PEAK PULSE CURRENT	REVERSE LEAKAGE @V _{RWM}
(UNI)	(BI)	UNI	BI	V _{RWM} (V)	V _{BR MIN} (V)	V _{BR MAX} (V)	I _T (mA)	V _C (V)	I _{PP} (A)	I _R (μA)
SMBJ70A	SMBJ70CA	NP	DP	70.0	77.8	86.00	1	113.00	5.30	1
SMBJ75A	SMBJ75CA	NR	DR	75.0	83.30	92.10	1	121.00	5.00	1
SMBJ78A	SMBJ78CA	NT	DT	78.0	86.70	95.80	1	126.00	4.80	1
SMBJ85A	SMBJ85CA	NV	DV	85.0	94.40	104.00	1	137.00	4.40	1
SMBJ90A	SMBJ90CA	NX	DX	90.0	100.00	111.00	1	146.00	4.10	1
SMBJ100A	SMBJ100CA	NZ	DZ	100.0	111.00	123.00	1	162.00	3.70	1
SMBJ110A	SMBJ110CA	PE	EE	110.0	122.00	135.00	1	177.00	3.40	1
SMBJ120A	SMBJ120CA	PG	EG	120.0	133.00	147.00	1	193.00	3.10	1
SMBJ130A	SMBJ130CA	PK	EK	130.0	144.00	159.00	1	209.00	2.90	1
SMBJ150A	SMBJ150CA	PM	EM	150.0	167.00	185.00	1	243.00	2.50	1
SMBJ160A	SMBJ160CA	PP	EP	160.0	178.00	197.00	1	259.00	2.30	1
SMBJ170A	SMBJ170CA	PR	ER	170.0	189.00	209.00	1	275.00	2.20	1
SMBJ180A	SMBJ180CA	PT	ET	180.0	201.00	222.00	1	292.00	2.10	1
SMBJ188A	SMBJ188CA	PV	EV	188.0	209.00	231.00	1	304.00	2.00	1
SMBJ200A	SMBJ200CA	PX	EX	200.0	224.00	247.00	1	324.0	1.9	1
SMBJ210A	SMBJ210CA	PZ	EZ	210.0	237.00	263.00	1	340.0	1.8	1
SMBJ220A	SMBJ220CA	QE	FE	220.0	246.00	272.00	1	356.0	1.7	1
SMBJ250A	SMBJ250CA	QG	FG	250.0	279.00	309.00	1	405.0	1.5	1
SMBJ300A	SMBJ300CA	QK	FK	300.0	335.00	371.00	1	486.0	1.3	1
SMBJ350A	SMBJ350CA	QM	FM	350.0	391.00	432.00	1	567.0	1.1	1
SMBJ400A	SMBJ400CA	QP	FP	400.0	447.00	494.00	1	648.0	0.9	1
SMBJ440A	SMBJ440CA	QR	FR	440.0	492.00	543.00	1	713.0	0.9	1

Note:

1. For Bi-directional type having V_{RWM} of 10 Volts and less, the I_R limit is double.
2. For parts without A, the V_{BR} is ± 10% and V_C is 5% higher than with A parts.

I-V Curve Characteristics



- P_{PPM} Peak Pulse Power Dissipation - Max power dissipation
- V_{RWM} Reverse Stand-off Voltage - Maximum voltage that can be applied to TVS without operation
- V_{BR} Breakdown Voltage – Maximum voltage that flows though the TVS at a specified current (I_T)
- V_C Clamping Voltage – Peak voltage measured across the TVS at a specified I_{PPM} (peak impulse current)
- I_R Reverse Leakage Current – Current measured at V_R
- V_F Forward Voltage Drop for Uni-directional

TYPICAL CHARACTERISTIC CURVES

Fig 1: Peak Pulse Power Rating




Fig 3: Pulse Derating Curve




Fig 2: Pulse Waveform






Fig 4: Typical Junction Capacitance



PACKAGE DETAILS

DO-214AA(SMB) PACKAGE OUTLINE AND DIMENSIONS



DIM	Millimeters		Inches	
	Min	Max	Min	Max
A	4.06	4.57	0.16	0.18
B	3.3	3.94	0.13	0.155
C	1.78	2.2	0.07	0.086
D	0.13	0.31	0.006	0.012
E	5.08	5.59	0.2	0.22
F	--	0.2	--	0.008
G	1.95	2.62	0.077	0.103
H	0.76	1.52	0.03	0.06

MECHANICAL CHARACTERISTICS

1. Polarity: Cathode band denotes uni-directional device, none cathode band denotes bi-directional device.
2. Terminal: Solder plated



Recommended Product Storage Environment for Discrete Semiconductor Devices

This storage environment assumes that the Diodes and transistors are packed properly inside the original packing supplied by CDIL.

- Temperature 5 °C to 30 °C
- Humidity between 40 to 70 %RH
- Air should be clean.
- Avoid harmful gas or dust.
- Avoid outdoor exposure or storage in areas subject to rain or water spraying .
- Avoid storage in areas subject to corrosive gas or dust. Product shall not be stored in areas exposed to direct sunlight.
- Avoid rapid change of temperature.
- Avoid condensation.
- Mechanical stress such as vibration and impact shall be avoided.
- The product shall not be placed directly on the floor.
- The product shall be stored on a plane area. They should not be turned upside down. They should not be placed against the wall.

Shelf Life of CDIL Products

The shelf life of products is the period from product manufacture to shipment to customers. The product can be unconditionally shipped within this period. The period is defined as 2 years.

If products are stored longer than the shelf life of 2 years the products shall be subjected to quality check as per CDIL quality procedure.

The products are further warranted for another one year after the date of shipment subject to the above conditions in CDIL original packing.

Floor Life of CDIL Products and MSL Level

When the products are opened from the original packing, the floor life will start.

For this, the following JEDEC table may be referred:

JEDEC MSL Level		
Level	Time	Condition
1	Unlimited	≤30 °C / 85% RH
2	1 Year	≤30 °C / 60% RH
2a	4 Weeks	≤30 °C / 60% RH
3	168 Hours	≤30 °C / 60% RH
4	72 Hours	≤30 °C / 60% RH
5	48 Hours	≤30 °C / 60% RH
5a	24 Hours	≤30 °C / 60% RH
6	Time on Label(TOL)	≤30 °C / 60% RH



Continental Device India Pvt. Limited

An IATF 16949, ISO9001 and ISO 14001 Certified Company



Customer Notes

Component Disposal Instructions

1. CDIL Semiconductor Devices are RoHS compliant, customers are requested to please dispose as per prevailing Environmental Legislation of their Country.
2. In Europe, please dispose as per EU Directive 2002/96/EC on Waste Electrical and Electronic Equipment (WEEE).

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered trademark of

Continental Device India Pvt. Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone +91-11-2579 6150, 4141 1112 Fax +91-11-2579 5290, 4141 1119

email@cdil.com www.cdil.com

CIN No. U32109DL1964PTC004291

SMBJXXX

Rev02_14042021ESW