

ALUMINUM ELECTROLYTIC CAPACITORS

UE series Chip Type, Vibration Resistance



- Chip type with load life of 2000 to 5000 hours at 125°C.
- Suited for automobile electronics where heavy duty services are indispensable.
- Compliant to the RoHS directive (2002/95/EC).




Specifications


Item	Performance Characteristics						
Category Temperature Range	-55 to +125°C (φ 12.5 to 20) -40 to +125°C (φ 8, φ 10)						
Rated Voltage Range	10 to 50V						
Rated Capacitance Range	33 to 4700μF						
Capacitance Tolerance	±20% at 120Hz, 20°C						
Leakage Current	After 1 minute's application of rated voltage, leakage current is not more than 0.03CV or 4 (μA), whichever is greater.						
Tangent of loss angle (tan δ)	For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.						
	Rated voltage (V)	10	16	25	35	50	120Hz
Stability at Low Temperature	Impedance ratio Z-40°C / Z+20°C (MAX)	φ 8 · φ 10	10	8	6	4	4
		φ 12.5 to φ 20	0.26	0.20	0.16	0.14	0.14
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 5000 hours (2000 hours for φ D=8 and 10) at 125°C.						
	Capacitance change	Within ±30% of the initial capacitance value					
Shelf Life	After storing the capacitors under no load at 125°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.						
	tan δ	300% or less than the initial specified value					
Marking	Black print on the case top.						
	Leakage current	Less than or equal to the initial specified value					

Chip Type

(φ8 to φ10)



Type numbering system (Example : 50V 330μF)



φD	8	10	12.5	16	18	20
A	2.9	3.2	4.8	5.4	6.4	6.2
B	8.3	10.3	13.6	17.1	19.1	21.1
C	8.3	10.3	13.6	17.1	19.1	21.1
E	3.1	4.5	4.0	6.3	6.3	8.8
H	1.1 to 1.5	1.1 to 1.5	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4	1.3 to 1.7

Dimensions

Cap.(μF)	Code	10		16		25		35		50	
		1A		1C		1E		1V		1H	
33	330									8×10	90
47	470									10×10	130
100	101			8×10	140	8×10	140	10×10	150	12.5×13.5	500
220	221	8×10	140	10×10	190	10×10	190	12.5×13.5	550	16×16.5	850
330	331	10×10	190	12.5×13.5	750	12.5×13.5	750	16×16.5	1000	16×16.5	850
470	471	12.5×13.5	750	12.5×13.5	750	16×16.5	1000	16×16.5	1000	18×16.5	950
680	681	12.5×16	900	16×16.5	1000	18×16.5	1200	18×16.5	1200		
						▲ 16×21.5	1200				
1000	102	12.5×16	900	18×16.5	1200	18×21.5	1550	20×21.5	1400		
2200	222	18×16.5	1200	18×16.5	1200						
		▲ 16×21.5	1200								
3300	332	18×16.5	1200								
4700	472	18×21.5	1550							Case size φD×L (mm)	Rated ripple

※ In this case, [6] will be put at 12th digit of type numbering system, "▲"

Rated ripple current (mA rms) at 125°C 100kHz

Frequency coefficient of rated ripple current

φ D	Cap.(μF)	Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
φ 8 · φ 10	33 to 330		0.47	0.67	0.78	0.91	1.00
	100 to 680		0.53	0.67	0.82	0.89	1.00
φ 12.5 to φ 20	1000 to 4700		0.74	0.87	0.96	0.98	1.00

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.