Shell style/model

Codes

Contact type

Free cable mount socket connector, female contact

Code 1

Solder type

100

CIRCULAR CONNECTORS

Push-pull connectors female cable mount CCT series


CCT2S1/05 5 pole

- Premium range of circular connectors
- IP68 sealed using vacuum technology (when connected and using environmental cable clamp)
- Tough, high performance interconnection solution
- · Ideal for harsh and extreme environments
- Suitable for broadcasting, autosport, military, rail, security and industrial applications
- Key coded to prevent misconnection
- Will not disconnect when the cable is under load or stress
- · Cable mounting
- Tested to IEC 60512-3-5a
- Cable clamp required for use with this series




SOCKETS

PART NO.	DESCRIPTION	POLES	SERIES
CCT2S1/05	Female cable	5	CCT series



Contact diameter	0.9mm
Max. stranded conductor	AWG 21-22
Max diameter	0.79mm
Vtest (contact-shell)	1100V(AC) 1900V(DC)
Vtest (contact-contact)	1400V(AC) 2200V(DC)
Rated current	6.8A
Rated voltage	≤250V
Mechanical operation	5000 mating cycles
Housing material	Brass (natural chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces
Insulator	PPS
Contacts	Brass (gold plated)
Humidity (max)	<=95% [at 60°C /140°F]
Vibration	15g [10 Hz - 2000 Hz]
Shock resistance	100g [6 ms]
Salt spray corrosion	>72 hr
Climatical category	50/175/21
Shielding (min)	75 dB (10 MHz)
Shielding (min)	40 dB (1 GHz)
IP rating	IP68 (when connected and using environmental cable clamp)



KEY FEATURES

Key coded | Cable mounting socket | Cable clamps required

This product should be used with the following cable clamps:

CCV2C/CE 3.7 - 4.2mm CCV2C/CG 4.2 - 4.7mm CCV2C/CH 4.7 - 5.2mm CCV2C/CI 5.2 - 5.7mm CCV2C/CJ 5.7 - 6.2mm



Non IP68 cable clamps also available

ACCESSORIES

Metal and rubber caps for sockets

PART NO.	DESCRIPTION
CCT21	Camcirc metal cap for sockets A2

DESCRIPTION
Camcirc rubber cap for sockets A2



ASSOCIATED PRODUCTS

CCA2P1/A05

- CCA Series A2 size plug

page 109