

Navigation

Getting Started Learning **Product**

Arduino

Shield

Grove

Kit

Xadow

Mbed

Support

Forum Wish

SeeedStudio

Taobao

Navigation

Main page Random page Recent changes

Collections

Motor Arduino

Grove Shield

Kit

Xadow

Toolbox

What links here Related changes Special pages Printable version Permanent link

Page FAQ Go Read View source View history Search Sea

ቆ Lo

Grove Starter Kit for mbed

(Redirected from Grove4mbed)

Contents [hide] 1 About mbed and Grove 2 About this kit 3 Get Started 3.1 Hello, world 3.2 Fruit Piano 3.2.1 Hardware 3.2.1.1 Software 3.3 More, Step By Step

About mbed and Grove

mbed is an open source development platform for rapid prototyping with microcontrollers. It provides free software libraries, hardware designs and development tools to build projects very easily and fast.

Grove is a modular electronics platform for quick prototyping that does not involve soldering or bread boarding.

About this kit

This kit is designed for you to get started with mbed as soon as possible. It contains many plug-n-play Grove modules to start exploring the mbed world. One goal is to have fun and build confidence with hardware and software in the journey.


Get Started

All the things to get started are:


- This kit
- An Arch
- A USB Micro B cable
- · A computer with Internet

Hello, world

- 1. Click this link at to signup or login mbed, then you will get the mbed online compiler.
- 2. Import the program and open main.cpp, you will see the code.



3. On mbed online IDE, click "Compile" of the top toolbar (or use CTRL + D) to compile the code and the binary file -Arch_GPIO_Ex1_LPC11U24.bin.



- 4. Connect the Arch board to the computer and long press the button, a USB drive named CRP DISABLD will pop up.
- 5. Delete firmware.bin and copy Arch_GPIO_Ex1_LPC11U24.bin to the USB drive.
- 6. Quick press the button, the program will be running, an LED will be blinking.

```
#include "mbed.h"
  Configure a GPIO pin as output for controlling a LED. 'led' is user assigned name and
 'LED1' is a internal name given to a port pin P1_8 in this Arch platform. */
DigitalOut led(LED1);
int main()
```


The above program uses **DigitalOut** class and **wait()** function of mbed C/C++ SDK. LED1 is an pseudonym of I/O pin **P1_8** and is labelled D1 in the Arch board. The state of LED1 is changed by writing either 0 or 1 to **led**. The **wait()** function produces a delay in seconds. The state of the **led** is continuous toggled every 0.5 seconds inside the endless **while()** loop.

More details of **DigitalOut** can be find in DigitalOut page of mbed handbook . Similarly the **wait()** function is documented in wait page .

Fruit Piano

A piano built with a basket of fruit, a microcontroller and a computer.

The idea is from Makey Makey &, but uses different hardware and software. An mbed enabled microcontroller with USB is used.





Hardware

- An Arch board
- A basket of fruit
- A computer with AC power
- Some wires

Software

- 1. Click this link at to import the program to mbed online compiler.
- 2. Compile the code and download the binary file Fruit_Piano_LPC11U24.bin.
- 3. Connect the Arch board to the computer and long press the button, a USB drive named CRP DISABLD will pop up.
- 4. Delete firmware.bin and copy Arch_GPIO_Ex1_LPC11U24.bin to the USB drive.
- 5. Quick press the button to run the program
- 6. Wire some apples or bananas to A0 A5 (P0_11 P0_14, P0_16, P0_22) pins of the Arch board
- 7. Open Fruit Piano de and play

More, Step By Step

- 1. Digital Input Button: use a button to control an LED
- 2. Analog Input Potentiometer: use a potentiometer to control the blinking of an LED &
- 4. PWM Ouput Buzzer: use a buzzer to play a melody 🗗
- 5. Display: make a digital clock 🗗

- 6. A thermometer 🗗
- 7. Infrared keyboard 🗗
- 8. Colorful light 🗗
- 9. Temperature controls color

This page was last modified on 26 August 2014, at 14:53.

This page has been accessed 456 times.

About Wiki Seeed Studio

