

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918

Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## **CAN FD 3 Click**





PID: MIKROE-3992

CAN FD 3 Click is a add-on board based on TLE9251V CAN network transceiver, designed for HS CAN networks up to 5 Mbit/s in automotive and industrial applications. As an interface between the physical bus layer and the CAN protocol controller, the TLE9251V drives the signals to the bus and protects the microcontroller against interferences generated within the network. Given all the features its components offer, the CAN FD Click is best used for for infotainment applications, gateway modules, body control modules (BCM) or engine control units (ECUs).

CAN FD 3 Click board™ is supported by a mikroSDK compliant library, which includes functions that simplify software development. This Click board™ comes as a fully tested product, ready to be used on a system equipped with the mikroBUS™ socket.

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.







MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com

www.mikroe.com

## **Specifications**

| Туре             | CAN  |
|------------------|--|
| Applications     | CAN FD Click is best used for for infotainment applications, gateway modules, body control modules (BCM) or engine control units (ECUs).     |
| On-board modules | On-board modules TLE9251V, a transceiver designed for HS CAN networks up to 5 Mbit/s in automotive and industrial applications from Infineon |
| Key Features     | Key Features Very low electromagnetic<br>emission (EME) for chokeless usage, Dual<br>Power Supply Solution                                   |
| Interface        | UART   |
| Compatibility    | mikroBUS   |
| Click board size | L (57.15 x 25.4 mm)  |
| Input Voltage    | 3.3V or 5V   |

## Resources

mikroBUS™

**mikroSDK** 

Click board™ Catalog

Click boards™

## **Downloads**

CAN FD 3 click example on Libstock

**CAN FD 3 click schematic** 

TLE9251V datasheet

CAN FD 3 click 2D and 3D files

Mikroe produces entire development toolchains for all major microcontroller architectures. Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



