

This document was generated on 08/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0511102051		
Status:	Active		
Overview:	Milli-Grid Connector System		
Description:		eceptacle Housing, 20 Circuits, with Center Polarization Key,	
	with Locking Ramp, Lead-F	166	
Decumenter			E-SXIM
Documents: 3D Model		Application Specification E02040004 AS 000 (DDE)	
		Application Specification 503940001-AS-000 (PDF) Packaging Specification PK-51110-300-001 (PDF)	
Drawing (PDF) 3D Model (PDF)		Brochure (PDF)	
· · · · ·	PS-51110-001-001 (PDF)	RoHS Certificate of Compliance (PDF)	Series image - Reference only
	<u>1 8-31110-001-001 (I DI)</u>		
Agency Certification	ı		<u>EU ELV</u>
CSA		LR19980	Compliant
UL		E29179	
			EU RoHS China RoHS
Application tooling			Compliant
Application Tooling P	art Link	63824-2800	REACH SVHC
General			Not Contained Per -
Product Family		Crimp Housings	D(2021)4569-DC (8
Series		51110	July 2021)
Application		Signal, Wire-to-Board	Halogen-Free
Comments		Applicable Wire Ranges: 24-30 AWG (series <u>50394</u>	<u>Status</u>
Comments		terminal) and 22-28 AWG (series <u>87396</u> terminal)	Not Low-Halogen
Overview		Milli-Grid Connector System	For more information, please visit <u>Contact US</u>
Product Name		Milli-Grid	China DOUS Croop Imaga
UPC		800753573888	China ROHS Green Image ELV Compliant
010		000700070000	RoHS Phthalates Not Contained
Physical			
Circuits (maximum)		20	
Color - Resin		Black	
Flammability		94V-0	Search Parts in this Series
Gender		Receptacle	<u>51110</u> Series
Glow-Wire Capable		No	
Keying to Mating Part	:	Yes	Mates With
Lock to Mating Part		Yes	Milli-Grid Headers <u>87758</u> , <u>87759</u> , <u>87760</u>
Material - Resin		Polyester	, <u>87831</u> , <u>87832</u> Milli-Grid BMI Header
Net Weight		0.425/g	151013 br>Milli-Grid Low-Halogen Headers
Number of Rows		2	<u>151117</u> , <u>151118</u> , <u>151119</u> , <u>151120</u>
Packaging Type		Bag	
Panel Mount		No	Use With
Pitch - Mating Interfac		2.00mm	Milli-Grid Crimp Terminals <u>50394</u> , <u>87396</u>
Pitch - Termination In		2.00mm	<pre> <br <="" td=""/></pre>
Polarized to Mating P	art	Yes	<u>797581095, 797581096</u>
Stackable		No	
Temperature Range -	Operating	-40° to +105°C	Application Tooling FAQ
Material Info			Tooling specifications and manuals are
			found by selecting the products below.
Reference - Drawing	Numbers		Crimp Height Specifications are then
Application Specificat		503940001-AS-000	contained in the Application Tooling
Packaging Specificati		PK-51110-300-001	Specification document.
Product Specification		PS-51110-001-001	Global
i roudot opcomoutori			

for Milli-Grid 2.0 Housings 638242800

This document was generated on 08/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION