

Computer Power Cord, Right-Angle NEMA 5-15P to C13 - Heavy-Duty, 15A, 125V, 14 AWG, 2 ft. (0.61 m), Black

MODEL NUMBER: **P007-002-15D**











Heavy-duty computer power cord connects a server, PC, monitor or printer to a surge protector, PDU or UPS with a NEMA 5-15R outlet.

Features

5-15P to C13 Power Cable for Network Devices That Require a Heavy-Gauge ConnectionThis computer power supply cable features 14 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. You can use it to connect a computer, server, monitor, laser printer or drive to an AC wall outlet, surge protector, UPS system or PDU. It can also replace or upgrade the standard power cord provided by the device's manufacturer. The 2-ft. (0.61 m) length helps reduce cable clutter and minimize the risk of tripping. Note: This cord is not for use in European markets.

Right-Angle PC Power Cable Is Easier to Connect in Tight SpacesThe angled NEMA 5-15P connector makes installations easier in confined spaces, such as the back of a rack enclosure cabinet. When plugged in, the right-angle plug guides the computer power supply cable parallel to the wall, allowing you to push furniture up against a wall to maximize space.

Highlights

- Right-angle 5-15P plug allows easier connection in confined or hard-to-reach spaces
- Recommended for powering larger servers, laser printers and other network devices
- 2-ft. (0.61 m) length allows flexibility in placing devices, while avoiding cable clutter
- Computer power cable replaces or upgrades original manufacturer's power cord
- Thick 14 AWG wire gauge manages high power levels required for larger equipment

Applications

- Connect devices like computers, large servers and laser printers to a PDU up to 2-ft. (0.61 m) away in your data center
- Extend an existing power connection up to 2-ft. (0.61 m) to more easily place a device or reach a power source in a rack
- Update or replace the standard power cord provided by a device's original manufacturer
- Power a device located in a hard-to-access area behind a desk or flush against a wall

Package Includes

 P007-002-15D Heavy-Duty Desktop Computer Power Cord, Right-Angle 5-15P to C13, 2-ft. (0.61 m), Black

Specifications

OVERVIEW		
UPC Code	037332241825	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	15	
Voltage Compatibility (VAC)	125	





Plug Color Black Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating FT2 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 NEMA 5-15P - RIGHT ANGLE FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes			
Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating FT2 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 6-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS Yes Angled Plug Yes Angled Plug Yes	PHYSICAL		
Cable Jacket Material PVC Cable Jacket Rating FT2 Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 2.08 Cable Length (ft.) 2 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Dimensions (hwd / in.) 0.12 ENVIRONMENTAL Operating Temperature Range 4 TO 140 F (- 20° TO 60°C) Storage Temperature Range 2.080% RH Storage Humidity Range 2.080% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS STANDARDS & COMPLIANCE			
Cable Jacket Rating FT2 Power Cord Jacket Type SJT Gable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range 2-4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE			
Power Cord Jacket Type SJT Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (fit.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Dimensions (hwd / in.) 0.12 ENVIRONMENTAL Operating Temperature Range 4 TO 140 F (-20° TO 60°C) Storage Temperature Range 4-1 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-16P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE		PVC	
Cable Outer Diameter (OD) 9.2mm Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 9.98 x 7.08 x 0.50 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range 4 TO 140 F (- 20° TO 60°C) Storage Temperature Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE		FT2	
Number of Conductors 3 Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Power Cord Jacket Type	SJT	
Wire Gauge (AWG) 14 Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Cable Outer Diameter (OD)	9.2mm	
Wire Gauge (OD - mm²) 2.08 Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Number of Conductors	3	
Cable Length (ft.) 2 Cable Length (m) 0.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) 0.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Wire Gauge (AWG)	14	
Cable Length (m) O.61 Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 Shipping Weight (kg) O.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Wire Gauge (OD - mm²)	2.08	
Shipping Dimensions (hwd / in.) 9.98 x 7.08 x 0.50 O.12 ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (-20° TO 60°C) Storage Temperature Range -4 TO 140 F (-20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Cable Length (ft.)	2	
Shipping Weight (kg) ENVIRONMENTAL Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Cable Length (m)	0.61	
ENVIRONMENTAL Operating Temperature Range	Shipping Dimensions (hwd / in.)	9.98 x 7.08 x 0.50	
Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Shipping Weight (kg)	0.12	
Operating Temperature Range -4 TO 140 F (- 20° TO 60°C) Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE			
Storage Temperature Range -4 TO 140 F (- 20° TO 60°C) Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE			
Operating Humidity Range 20-80% RH Storage Humidity Range 20-80% RH CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE			
CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE		-4 TO 140 F (- 20° TO 60°C)	
CONNECTIONS Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Operating Humidity Range	20-80% RH	
Side A - Connector 1 NEMA 5-15P - RIGHT ANGLE Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Storage Humidity Range	20-80% RH	
Side B - Connector 1 IEC-320-C13 FEATURES & SPECIFICATIONS High Voltage Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	CONNECTIONS		
FEATURES & SPECIFICATIONS High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Side A - Connector 1	NEMA 5-15P - RIGHT ANGLE	
High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	Side B - Connector 1	IEC-320-C13	
High Voltage Yes Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE	FEATURES & SPECIFICATIONS		
Locking Plug No Angled Plug Yes STANDARDS & COMPLIANCE		Yes	
Angled Plug Yes STANDARDS & COMPLIANCE		No	
STANDARDS & COMPLIANCE		Yes	
		1.1. C.	
	Certifications		
Approvals UL /CSA	Approvals	UL/CSA	
WARRANTY			
Product Warranty Period (Worldwide) Lifetime limited warranty	Product Warranty Period (Worldwide)	Lifetime limited warranty	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies