



Search:

Go

Products

Catalogs

Search

Customer Support

About Cannon

Home

SMB



PART NUMBER: B51-328-3188220

Image Disclaimer:
Please use Customer Drawing for design activity: line art and other pictures are general representations of product dimensions.

[View Line Drawings](#)



- [Sales Support](#)
- [Ask a Specialist](#)
- [Product Home](#)
- [Stock Check](#)

Product Family	RF
Product Group	RF - SMB
Market Application	Military, Industrial
Component Type	90° Plugs
Gender	Plug
Mounting Style	90°
Coaxial Cable Type	RG174/U, RG316/U
Engagement (Insertion) Force	Initial = 62 N (14 lbs.) maximum engagement.
Packaging Type	Each
Plating	Center contact: Gold. Other metal parts: Gold to meet the finish and corrosion requirements of MIL-C-39012.
Product Description	90° Crimp Plug
Cable Retention	When properly assembled to the compatible braided coaxial cable, the retention is equal to the breaking strength of the cable.
Connector Durability	500 mating cycles minimum
Contact Current Rating	1.5 A DC maximum
Corrosion (salt spray)	MIL-STD-202, Method 101, test condition B, 5% salt solution
Insertion Loss	0.25 dB maximum @ 4 GHz
Insulation Resistance	1000 M ohms minimum
Locknut Torque	0.56 to 0.64 Nm (80 to 90 in. oz.)
Moisture Resistance	MIL-STD-202, Method 106, when interface gasket is used. No measurement at high humidity. Insulation resistance shall be 200 M ohms minimum within five minutes after removal from humidity.
RF Leakage	-55 dB minimum @ 2-3 GHz
Shock	MIL-STD-202, Method 213, Test Condition B, 75 G`s at 6 milliseconds 1/2 sine.
Temperature Rating	-65°C to 165°C
Thermal Shock	MIL-STD-202, Method 107, Test Condition B, except high temperature shall be 85°C. High temperature shall be 200°C for connectors using 200°C cables.
Vibration, High Frequency	MIL-STD-202, Method 204, Test Condition B (15 G`s)

Impedance	50 ohms
Frequency Range 1	0 to 4.0 GHz
Contact Resistance	Center contact = 6.0 m ohms maximum initial. 8.0 m ohms maximum after environment. Outer contact = 1.0 m ohms maximum initial. 1.5 m ohms maximum after environment. Braid to body = 1.0 m ohms maximum
Engagement Design	MIL-C-39012, Series SMB
Material	Body, body components and male contacts: Brass, half hard. Female contacts: Beryllium copper, heat treated. Insulators: PTFE. Lockwashers: Phosphor bronze. Crimp ferrule: Annealed copper alloy. Gaskets: Silicone rubber.
Contact Retention	Unless specified otherwise, all connectors feature captivated contacts. When captivated the contacts will withstand 17,8 N (4.0 lbs.) minimum axial force. CECC 2213 = 10 N (2.25 lbs.).
Assembly Instructions	BAI-015
For more information	Please Contact Cannon Sales Department .
Footnote	Dimension are shown in mm (inch). Dimensions subject to change.
Note	SMB connectors have solder center contacts.

