

Standard extruded heatsinks

<p>art. no.</p> <p>SK 19 ...</p>		
<p>please indicate: (optional)</p> <p>37.5 50 75 100 1000 mm TO 3; CB</p>		
<p>art. no.</p> <p>SK 28 ...</p>		
<p>please indicate: (optional)</p> <p>37.5 50 75 1000 mm TO 3; CB</p>		
<p>art. no.</p> <p>SK 401 ...</p>		
<p>please indicate: (optional)</p> <p>100 1000 mm TO 3; CB</p>		
<p>art. no.</p> <p>SK 72 ...</p>		
<p>please indicate: (optional)</p> <p>37.5 50 75 100 1000 mm TO 3; CB</p>		
<p>art. no.</p> <p>SK 04 ...</p>		
<p>with slots for cover plates or PCBs</p> <p>please indicate: (optional)</p> <p>37.5 50 75 100 1000 mm TO 3; CB; SSR 1; SSR 2</p>		

Hole pattern
Profiles for PCB components
Heatsinks for PCB
Profiles for PCB mounting

→ A 21
→ A 91
→ A 89
→ A 89 - 111

Silicone wafers
Thermal conductive material
Kapton insulator washers

→ E 2 - 4
→ E 2 - 15
→ E 8