

This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0022035055		
Status:	Active		
Overview:	Mini-SPOX Wire-to-Boa	ard Connector System	
Description:	2.50mm Pitch, Mini-SP	OX PCB Header, Single Row, Vertical, Through Hole, Tin , 3.50mm PC Tail Length	
Documents:			
<u>3D Model (PDF)</u>		Product Specification 52641001-PS-000 (PDF)	
3D Model		Product Specification PS-5264-001-001 (PDF)	
2D Drawing (DXF)		Packaging Specification SPK-5267-001-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Series image - Reference only
2D Drawing DXF (PI	<u>DF)</u>		
. .	,		EU ELV
Agency Certificatio	n		Not Relevant
CSA		LR19980	
UL		E29179	EU RoHS China RoHS
Conoral			Compliant
General		DOD Llandern	REACH SVHC
Product Family		PCB Headers	Not Contained Per -
Series		<u>5267</u>	D(2021)4569-DC (8
Application		Signal, Wire-to-Board	July 2021)
Overview		Mini-SPOX Wire-to-Board Connector System	Halogen-Free
Product Name		Mini-SPOX	<u>Status</u>
UPC		800753591516	Not Low-Halogen
Physical			For more information, please visit Contact U
Breakaway		No	China ROHS Green Image
Circuits (Loaded)		5	ELV Not Relevant
Circuits (maximum)		5	RoHS Phthalates Not Contained
Color - Resin		Natural	Not Service and the service an
Durability (mating cy	cles max)	30	
First Mate / Last Break		No	
Flammability		94V-0	Search Parts in this Series
Glow-Wire Capable		No	<u>5267</u> Series
Guide to Mating Parl		No	
Keying to Mating Part		None	Mates With
Lock to Mating Part		Yes	Mini-SPOX Receptacle Housing 5264
Material - Plating Mating		Tin	
Material - Plating Te	0	Tin	
Material - Resin		Nylon	
Net Weight		452.800/mg	
Number of Rows		1	
Orientation		Vertical	
PC Tail Length		3.50mm	
PCB Locator		No	
PCB Retention		Yes	
PCB Thickness - Re	commended	1.60mm	
Packaging Type		Bag	
Pitch - Mating Interfa	се	2.50mm	
Plating min - Mating		4.064µm	
Plating min - Termina	ation	4.064µm	
Polarized to Mating I		Yes	
Polarized to PCB	~	No	
Shrouded		Fully	
SHIDUDED			
		Νο	
Stackable Surface Mount Com	patible (SMC)	No No	

Termination Interface: Style Through Hole Electrical Current - Maximum per Contact 3.0A Voltage - Maximum 250V **Material Info Engineering Number** 5267-05A **Reference - Drawing Numbers** Packaging Specification SPK-5267-001-001 **Product Specification** 52641001-PS-000, PS-5264-001-001 Sales Drawing 52670001-SD-000

This document was generated on 12/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION