

Part Number: 1200170003

Product Description: Micro-Change (M12) to Nano-Change Snap Adapter, 4 Poles, 44.7mm

Length

Series Number: 120017

**Status:** Active

**Product Category:** Circular Industrial

Connectors

**Engineering Number: 854030** 



#### **Documents & Resources**

#### **Drawings**

Drawing 1200170003\_sd.pdf

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <u> </u>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21             |
| REACH SVHC         | Contains Lead per D(2020)4578-DC<br>(25 June 2020) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863   |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

# **Part Details**

## General

| Status         | Active  |
|----------------|---|
| Category       | Circular Industrial Connectors  |
| Series         | 120017  |
| Description    | Micro-Change (M12) to Nano-<br>Change Snap Adapter, 4 Poles,<br>44.7mm Length |
| Approvals      | N/A   |
| IP Rating      | IP67  |
| Product Family | Brad Micro-Change (M12)<br>Connectors   |
| Product Name   | Micro-Change (M12),Nano-Change (M8)   |
| Туре           | In-Line Interconnect  |
| UPC            | 883906144647  |

## Electrical

| Current - Maximum per Contact | N/A |
|-------------------------------|-----|
| Voltage - Maximum             | 60V |

# Physical

| Cable Diameter            | N/A                 |
|---------------------------|---------------------|
| Coupling Type             | N/A                 |
| Diagnostics / LEDs        | No                  |
| Diagnostics Port          | No                  |
| Gender                    | Female-Male         |
| Keyway                    | Single              |
| Material - Connector Body | PUR                 |
| Material - Contact        | Brass               |
| Material - Coupling Nut   | Nickel-plated Brass |
| Material - Plating Mating | Gold                |

| Net Weight                    | 16.830/g       |
|-------------------------------|----------------|
| Orientation                   | Straight       |
| Poles                         | 4              |
| Temperature Range - Operating | -25°C to +85°C |
| Wire Size (AWG)               | N/A            |

This document was generated on Mar 23, 2024