

This document was generated on 02/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	<u>0532530570</u>		
Status:	Active		
			11.
Overview: <u>Micro-Latch Wire-to-Board C</u>			
Description:	2.00mm Pitch, Micro-Latch F	PCB Header, Single Row, Vertical, Through Hole, Tin (Sn)	
	Plating, 5 Circuits, Tray, 3.50	Omm PC Tail Length	44
Documents:			
		Draduct Specification 510651000 DS 000 (DDF)	
<u>3D Model (PDF)</u>		Product Specification 510651000-PS-000 (PDF)	
<u>3D Model</u>		Packaging Specification SPK-53253-001-001 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
Product Specification	510650000-PS-000 (PDF)	Product Literature (PDF)	Series image - Reference only
Agency Certification	1		EU ELV
		E29179	Not Relevant
General			EU RoHS China RoHS
Product Family		PCB Headers	Compliant
Series		53253	REACH SVHC
Application		Signal, Wire-to-Board	Not Contained Per -
Overview		Micro-Latch Wire-to-Board Connector System	
Product Name		Micro-Latch Wire-to-Board Connector System Micro-Latch	D(2020)9139-DC (19
			Jan 2021)
UPC		756054354032	Halogen-Free
Dhusiaal			<u>Status</u>
Physical		N1.	Not Low-Halogen
Breakaway		No	For more information, please visit Contact US
Circuits (Loaded)		5	
Circuits (maximum)		5	China ROHS Green Image
Durability (mating cycles max)		30	ELV Not Relevant
First Mate / Last Break		No	RoHS Phthalates Not Contained
Glow-Wire Capable		No	
Lock to Mating Part		Yes	
Material - Metal		Brass	
Material - Plating Mating		Tin	Search Parts in this Series
Material - Plating Termination		Tin	<u>53253</u> Series
Material - Resin		Nylon	
Net Weight		204.000/mg	Mates With
5		5	51065 Crimp Housing, 50212 Crimp
Number of Rows		1	Terminal
Orientation		Vertical	Terminar
PC Tail Length		3.50mm	
PCB Locator		No	
PCB Retention		Yes	
PCB Thickness - Recommended		1.60mm	
Packaging Type		Tray	
Pitch - Mating Interface		2.00mm	
Plating min - Mating		1.016µm	
Plating min - Termination		1.016µm	
Polarized to Mating Part		Yes	
Polarized to PCB		No	
Shrouded			
		Partial	
Stackable		No	
Surface Mount Compatible (SMC)		No	
Temperature Range - Operating		-40° to +105°C	
Termination Interface:	: Style	Through Hole	
Electrical			
Current - Maximum pe	er Contact	2.0A	
Voltage - Maximum		125V	

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

SPK-53253-001-001 510650000-PS-000, 510651000-PS-000 532530000-SD-000

This document was generated on 02/27/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION