

Jun.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C
	VOLTAGE	300 V AC	OPERATING HUMIDITY RANGE	—
	CURRENT	2 A	APPLICABLE CABLE	
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK		APPROVED	KI. AKIYAMA	06.06.19
		CHECKED	SI. TOMIOKA	06.06.16
		DESIGNED	HM. SAITO	06.06.15
		DRAWN	HM. SAITO	06.06.15
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-019559-01	
	SPECIFICATION SHEET	PART NO.	PCN10-96S-2. 54C	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL583-0100-3-00	1/1