

RoHS


559/560 Series Fuse Blocks for TE5/TR5 Type Fuses




Agency Approvals				
Agency	Agency File Number			
	559 Series	560 Series		
	N/A	40041024		
7 1	N/A	E14721		

Dimensions units in mm

559 Series



560 Series



Product Characteristics				
	559 Series (Lead Free)	560 Series		
Compatible Fuses	TR5/TE5	TR5/TE5		
Materials	Holder: Black Thermoplastic, UL94 V-0	Holder: Thermoplastic, UL 94 V-0		
	Metal Parts: Copper alloy; solderable tinned			
Electrical Data (23°C)	Rated Voltage: 250V			
	Max. Current/Power: 6.3 A /1.6 W			
Mounting	PC Board, 7.18 mm pin spacing	PC Board, 5.08 mm pin spacing		
Solderability	max. 260 °C, 10 s (Wave)			
Minimum Cross Section	Conducting path - 0.1 mm ²			
Unit Weight	0.63 g	0,4 g		

Ordering Information

Ordering Number	"A" Height Options	Packaging
5590000001	6.5 mm (code 0001)	1000 Pcs Bulk
55900008011	10 mm (code 8011)	100 Pcs Bulk
5600001319	3.0 mm (code 1319)	500 Pcs Bulk
5600001009	4.3 mm (code 1009)	500 Pcs Bulk
56000001019	4.3 mm (code 1019)	1000 Pcs Bulk

Additional Information



Ð

Datasheet

560 Series



Resources

560 Series



Samples 559 Series



Samples 560 Series

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littlefuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littlefuse.com/disclaimer-electronics.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Littelfuse:

<u>56000001009</u> <u>55900000001</u> <u>56000001019</u> <u>56000001319</u> <u>55900000000</u> <u>5600000101</u> <u>5600000100</u> <u>5600000131</u>