



**RoHS
Compliant**

Specifications



Current Rating	: 20 Amp AC300V
Insulation withstands Volt	: AC2000V min.
Insulation Resistance	: >2000MΩ DC500V
Operation Temperature	: -40°C to +120°C
Wire Range	: 12AWG to 22AWG
Screw Torque	: 12lb-inch

Diagram



Dimensions : Millimetres

Pitch: 9.5mm		
Poles	A	B
2	22mm	9.5mm
3	31.5mm	19mm
5	50.5mm	38mm
7	69.5mm	57mm
9	88.5mm	76mm

SL	Material		Plating/Finish	Remark
1	Insulating Body	PBT(UL94V-0)	-	Black
2	Terminal	Brass	Tin Plated	-
3	Screw	Steel	Ni Plated	-
4	Cover	PC	-	-

Part Number Table

Description	Part Number
Barrier Terminal Block, 9.5mm, 20A 300V, with cover, 2 Poles	MC002075
Barrier Terminal Block, 9.5mm, 20A 300V, with cover, 3 Poles	MC002076
Barrier Terminal Block, 9.5mm, 20A 300V, with cover, 5 Poles	MC002077
Barrier Terminal Block, 9.5mm, 20A 300V, with cover, 7 Poles	MC002078
Barrier Terminal Block, 9.5mm, 20A 300V, with cover, 9 Poles	MC002079

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro