

This document was generated on 02/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Overview: Description:	0705530040 Active SL Modular Connectors 2.54mm Pitch SL Head Shrouded, 6 Circuits, T	er, Low Profile, Single Row, Right Angle, 3.05mm Pocket,	
Documents: 3D Model Drawing (PDF) Product Specification I Product Specification I		Packaging Specification PK-70873-0015-001 (PDF) Test Summary TS-70541-100-001 (PDF) RoHS Certificate of Compliance (PDF)	Series image - Reference only
Agency Certification CSA UL		LR19980 E29179	EU ELV Not Relevant
General Product Family Series Application Overview Product Name UPC		PCB Headers <u>70553</u> Signal, Wire-to-Board <u>SL Modular Connectors</u> SL 800753597440	EU RoHSChina RoHSCompliantREACH SVHCNot Contained Per -D(2020)9139-DC (19)January 20Halogen-FreeStatus
Physical Breakaway Circuits (Loaded) Circuits (maximum) Color - Resin Durability (mating cycl	es max)	No 6 6 Black 25	Not Low-HalogenFor more information, please visit Contact IChina ROHSGreen ImageELVNot RelevantRoHS PhthalatesNot Contained
Flammability Glow-Wire Capable Guide to Mating Part Lock to Mating Part Material - Metal Material - Plating Matin	ng	94V-0 No Yes Yes Brass, Phosphor Bronze Tin	Search Parts in this Series 70553 Series Mates With SL Crimp Housing 70066 Option N, 7006
Material - Plating Term Material - Resin Net Weight Number of Rows Orientation PC Tail Length PCB Locator	mation	Tin High Temperature Thermoplastic 1.310/g 1 Right Angle 3.30mm No	Option G, <u>70430</u> Option G, <u>70400</u> Option
PCB Retention PCB Thickness - Reco Packaging Type Pitch - Mating Interfact Plating min - Mating Plating min - Terminat	e	None 1.60mm Tube 2.54mm 3.810µm 3.810µm	
Plating min - Terminat Polarized to Mating Pa Shrouded Stackable Temperature Range - Termination Interface:	art Operating	3.810µm Yes Fully No -40° to +105°C Through Hole	
Electrical			

Current - Maximum per Contact

Voltage - Maximum	250V
Solder Process Data Lead-freeProcess Capability	WAVE
Material Info Engineering Number	A-70553-0040
Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing Test Summary	PK-70873-0015-001 PS-70400-001, PS-70541-001 SDA-70553-XXXX-001 TS-70541-100-001

This document was generated on 02/12/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION