Terminal Block
2.5mm²

multicomp PRO

RoHS Compliant

Features:

- Suitable for broad range of cross-section and types of wires
- Wires can be connected without any special preparation
- Easy for the extension of terminal connection
- Easy of handling and safe connection
- An excellent vibration proof protection against loosening
- High reliability and maintenance free
- Very low contact resistance
- Easy mounting and dismounting from the terminal rail

Specifications:

Material / Available Colour	: Beige
Insulation Stripping Length	: 10mm to 12mm
Clamping Screw (M)	: M3
Torque (lb-in)	: 7
Insulating Impulse Voltage Withstand	: 8KV
IEC	: 600V / 24A / AWG 10-22

Rail Dimensions

For TS35 × 7.5	: 5mm × 60mm × 47.5mm (T/W/H)
For TS35 × 15	: 5mm × 60mm × 55mm (T/W/H)

Accessories Table:

Type	Cat. No	Qty.
End Bracket	SEW35 CEW35/2	50 50
End Plate	CEP1	50
Partition	CEP5	50
Cross Jumper	CQV 2.5/2 CQV 2.5/3 CQV 2.5/4 CQV 2.5/10	50 50 50 20
Comb Link	CQB 2.5/2 CQB 2.5/3 CQB 2.5/10	50 50 20
Warning Cover	WS-2.5	50
Marking Tags	W5 W5Z W5K W7 W7Z W7K	500 400
Test Plug	TPS2.0 (ø2.0) TPS2.3 (ø2.3)	20 20
Socket	TPS2.0 TPS2.3	50 50
Protection Cover	DP1	20
Retaining Plates	AD1	50
Tool	DS3	-

Part Number Table

Description	Part Number
Terminal Block, DIN, 2.5mm²	CDU2.5

multicomp PRO