

Standard Rectifier

$$V_{RRM} = 2 \times 1200V$$


$$I_{FAV} = 25A$$

$$V_F = 1.16V$$


Phase leg

Part number

DSP25-12A



Backside: anode/cathode



Features / Advantages:

- Planar passivated chips
- Very low leakage current
- Very low forward voltage drop
- Improved thermal behaviour

Applications:


- Diode for main rectification
- For single and three phase bridge configurations

Package: TO-247

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0


Rectifier				Ratings		
Symbol	Definition	Conditions	min.	typ.	max.	Unit
V_{RSM}	max. non-repetitive reverse blocking voltage				1300	V
V_{RRM}	max. repetitive reverse blocking voltage				1200	V
I_R	reverse current, drain current	$V_R = 1200\text{ V}$			40	μA
		$V_R = 1200\text{ V}$			1.5	mA
V_F	forward voltage drop	$I_F = 25\text{ A}$			1.23	V
		$I_F = 50\text{ A}$			1.47	V
		$I_F = 25\text{ A}$			1.16	V
		$I_F = 50\text{ A}$			1.50	V
I_{FAV}	average forward current	$T_C = 135^\circ\text{C}$			25	A
		180° sine				
V_{FO}	threshold voltage	} for power loss calculation only			0.81	V
r_F	slope resistance				13.8	m Ω
R_{thJC}	thermal resistance junction to case				0.9	K/W
R_{thCH}	thermal resistance case to heatsink			0.25		K/W
P_{tot}	total power dissipation				160	W
I_{FSM}	max. forward surge current	$t = 10\text{ ms; (50 Hz), sine}$			300	A
		$t = 8,3\text{ ms; (60 Hz), sine}$			325	A
		$t = 10\text{ ms; (50 Hz), sine}$			255	A
		$t = 8,3\text{ ms; (60 Hz), sine}$			275	A
I^2t	value for fusing	$t = 10\text{ ms; (50 Hz), sine}$			450	A ² s
		$t = 8,3\text{ ms; (60 Hz), sine}$			440	A ² s
		$t = 10\text{ ms; (50 Hz), sine}$			325	A ² s
		$t = 8,3\text{ ms; (60 Hz), sine}$			315	A ² s
C_J	junction capacitance	$V_R = 400\text{ V; } f = 1\text{ MHz}$			10	pF

Package TO-247			Ratings			
Symbol	Definition	Conditions	min.	typ.	max.	Unit
I_{RMS}	RMS current	per terminal			70	A
T_{stg}	storage temperature		-55		150	°C
T_{vj}	virtual junction temperature		-40		175	°C
Weight				6		g
M_D	mounting torque		0.8		1.2	Nm
F_C	mounting force with clip		20		120	N

Product Marking



Ordering	Part Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	DSP25-12A	DSP25-12A	Tube	30	463604

Similar Part	Package	Voltage class
DSP25-12AT	TO-268AA (D3Pak) (2)	1200
DSP25-16A	TO-247AD (3)	1600
DSP25-16AR	ISOPLUS247 (3)	1600
DSP25-16AT	TO-268AA (D3Pak) (2)	1600

Equivalent Circuits for Simulation
** on die level*
 $T_{vj} = 175^{\circ}C$

Rectifier

$V_{0\ max}$	threshold voltage	0.81	V
$R_{0\ max}$	slope resistance *	11.2	mΩ

Outlines TO-247



Rectifier




Fig. 1 Forward current versus voltage drop per diode




Fig. 2 Surge overload current




Fig. 3 I^2t versus time per diode




Fig. 4 Power dissipation vs. direct output current and ambient temperature




Fig. 5 Max. forward current vs. case temperature




Fig. 6 Transient thermal impedance junction to case

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.03	0.0004
2	0.08	0.002
3	0.2	0.003
4	0.39	0.03
5	0.2	0.29