



Specifications


Connection in Acc. with standard EN-VDE

Nominal Current I _N	: 25Amp
Nominal Cross Section	: 6mm ²
Maximum load current	: 25A
Insulating Material	: PA

Dimensions

Pitch	: 9.52mm
Poles	: 2 and 3
Housing Material	: PA 66
Cage Clamp	: Steel, Ni Plated
Contact	: Brass, Tin Plated
Screw Thread	: M3.0, Steel, Zinc Plated
Wire Size	: 10AWG to 24AWG
Wire Strip Length	: 8mm
PCB Hole Diameter	: 1.7mm
Tightening Torque	: 9lb-inch Max.
Operating Temperature	: -40°C to +105°C

Diagram



Dimensions : Millimetres (Inches)

Part Number Table

Description	Part Number
PCB Terminal Block, 9.52mm, Modular Type, 30A 300V, 2 poles	MC002069
PCB Terminal Block, 9.52mm, Modular Type, 30A 300V, 3 poles	MC002070

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.