

PRODUCT-DETAILS

# Sentry USR10

## Sentry USR10 Safety relay



### General Information

Extended Product Type	Sentry USR10
Product ID	2TLA010070R0000
EAN	7350024483376
Catalog Description	Sentry USR10 Safety relay

Sentry USR10 Universal safety relay with delayable relay outputs 3NO+1NC, +24 VDC power supply and screw terminals.

For monitoring of safety devices with contacts, 1 or 2 equivalent or antivalent channels, safety devices with OSSD outputs, two-hand devices, safety mats and safety edges/bumpers.

Timer function 0-999 seconds with a better accuracy than 1%: OFF-delay, ON-delay, Time bypass and Time reset.

A display on front facilitates configuration and troubleshooting by displaying error codes and error log. A custom configuration can be protected by password. Manual or automatic reset selectable.

### Long Description

Sentry safety relays cover various types of safety applications up to PLe / SIL3. Basic models provide reliable supervision of simpler safety functions, while universal models provide advanced features and high flexibility.

Models with display offer preset configurations and extensive information to further simplify troubleshooting.

Additional variants offer a high accuracy timer function of  $\pm 1\%$  and an adjustable time setting range from 0-999 s.

High output current capacity of up to 6 A can save the use of an intermediary contactor. Multi-reset allows up to 10 safety relays connected to one reset light-button.

All models are available with detachable push-in or screw terminals. Terminals and coding kit to mark removed terminals are available as accessories.

---

## Ordering

---

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

---



---

## Popular Downloads

---

Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010072M0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010016T0001
Marketing Video	2TLC010019N0201 2TLC010018N0201

---



---

## Dimensions

---

Product Net Depth / Length	120 mm
Product Net Height	120 mm
Product Net Width	22.5 mm
Product Net Weight	0.229 kg

---



---

## Technical

---

Degree of Protection	IP20
Number of Outputs	Failsafe (Relay) 4
Performance Level (PL)	Up to e
Rated Control Supply Voltage (U <sub>s</sub> )	24 V DC

---



---

## Certificates and Declarations (Document Number)

---

CQC Certificate	CQC2017010303977544
cUL Certificate	2TLC010006D0201
cULus Certificate	2TLC010007D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Declaration of Conformity - UKCA	2TLC010190D0201
Instructions and Manuals	2TLC010072M0201
KC Certificate	2TLC010048D0201
RoHS Information	2TLC010010D0201
TÜV Certificate	2TLC010008D0201

---



---

## Classifications

---

Object Classification Code	K
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
ETIM 8	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
E-Number (Finland)	2712531

---

## Categories

---

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Safety Relays → Safety Timers

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Safety Relays → Universal Safety Relays

Low Voltage Products and Systems → Control Products → Safety Products → Safety Relays → Safety Timers

Low Voltage Products and Systems → Control Products → Safety Products → Safety Relays → Universal Safety Relays

