Note: This datasheet may be out of date Please download the latest datasheet of LQH43NN222J03# from the official website of Murata Manufacturing

## LQH43NN222J03#

"#" indicates a package specification code.

It can be used in 105 °C environment.

















< List of part numbers with package codes > LQH43NN222J03K LQH43NN222J03L



# Appearance & Shape





A: 3.5 max

(in mm)





#### References

| Packaging | Specifications   | Minimum Order<br>Quantity |
|-----------|------------------|---------------------------|
| K         | 330Embossed Tape | 2500                      |
| L         | 180Embossed Tape | 500                       |

| Mass (typ.) |       |
|-------------|-------|
| 1 piece     | 0.13g |



When rated current is applied to the products, selftemperature rise shall be limited to 20°C max and inductance will be within ±10% of initial inductance value.

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.

Please download the latest datasheet of LQH43NN222J03# from the official website of Murata Manufacturing Co., Ltd.

## LQH43NN222J03#

"#" indicates a package specification code.



| L size  | 4.5±0.3mm      |
|---|----------------|
| W size  | 3.2±0.2mm      |
| T size  | 2.6±0.2mm      |
| Size code inch (mm)                               | 1812 (4532)    |
| Inductance  | 2200µH±5%      |
| Inductance Test Frequency                         | 1kHz           |
| Rated current (Itemp) (Based on Temperature rise) | 30mA           |
| Max. of DC resistance                             | 50Ω            |
| Class of magnetic shield                          | No Shield      |
| Q(min.)   | 40             |
| Q Test Frequency                                  | 252kHz         |
| Self resonance frequency (min.)                   | 1.3MHz         |
| Operating Temperature Range                       | -40°C to 105°C |
| Series  | LQH43NN_03     |

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




## LQH43NN222J03#

"#" indicates a package specification code.





Impedance - Current Characteristics



Q-Frequency Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

