

DX07550B10N19510

Product Details

Part Number	DX07550B10N19510
Status	Active
Features	Cable harnesses, USB 3.2 Gen2 Type-C to Type-C, With screw lock TPE Black, Length: 1 m
Number of Positions	24 pos.
Rated Current	5 A max.
Rated Voltage	AC 20 Vr.m.s.
Applicable Specifications	USB 3.2
Waterproof/ Non-waterproof	
Applications	Smartphones, tablets, notebook PCs, TV, monitor, gaming devices, external storage mediums, digital cameras, and other small portable devices and industrial equipment
Connector Type	Cable harnesses
Connector Style	
PCB Mounting Method	-
Replacement	
USB-IF Certification	To be certified
TID	TBD
Mounting Type	-
Center Height	-

Recommended Board

Thickness	-
Finish of Contact in Connecting Area	ニッケル上ニッケル-パラジウム合金上金フラッシュめっき
Shell	
Contact Resistance	40 mΩ 以下 初期
Dielectric Withstanding Voltage	AC 40 Vr.m.s. (1分間)
Insulation Resistance	10 MΩ 以上
Operating Temperature Range	-20 °C to +50 °C
Mating Cycles	10,000 回
Packaging Type	
Quantity in The Standard Packaging	
Documents	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> Catalog </div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"> PDF Download </div> </div>
Stock Search	<div style="border: 1px solid #ccc; padding: 5px; display: inline-block;"> Stock Search > </div>
RoHS compliant	10 substances (2011/65/EU)
REACH compliant	
Environment Information	
Remarks	

Notice

- The values specified in this web site are only for reference. The products and their specifications are subject to change without notice. Contact our sales staff for further information before considering or

ordering any of our products.

For purchase, a product specification must be agreed upon.

2. Users are requested to provide protection circuits and redundancy circuits to ensure safety of the equipment, and sufficiently review the suitability of JAE's products to the equipment.
3. The products presented in this web site are designed for the uses recommended below.

We strongly suggest you contact our sales staff when considering use of any of the products in any other way than the recommended applications or for a specific use that requires an extremely high reliability.

(1) Applications that require consultation:

* Please contact us if you are considering use involving a quality assurance program that you specify or that is peculiar to the industry, such as:

Automotive electrical components, train control, telecommunications devices (mainline), traffic light control, electric power, combustion control, fire prevention or security systems, disaster evention equipment, etc.

* We may separately give you our support with a quality assurance program that you specify, when you think of a use such as :

Aviation or space equipment, submarine repeaters, nuclear power control systems, medical equipment for life support, etc.

This site uses cookies to improve its performance, enhance your user experience and tailor advertising. By using this site you consent to the use of cookies as described in our usage policy unless you have changed your cookie settings. Please click [here](#) for more information.

Accept and Hide This Message

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JAE Electronics:](#)

[DX07550B10N19510](#)